

## Saratoga Neutral Silicone Sealant with Anti-mould protection Technical Data Sheet

Saratoga Neutral Silicone Sealant with Anti-mould protection is a neutral one-component silicone sealant, that cures quickly thanks to the atmospheric humidity, creating extremely elastic and adhesive seals.

It is pure silicone, does not contain solvents, and is odourless.

Especially formulated for sealing glass and plastic materials, is also suitable for fixing mirrors, and treated and reflecting glasses.

Extremely resistant to UV rays and atmospheric agents, excellent elastic recovery after elongation and pressure, high resistance to moulds, fungi, ozone and low and high temperatures.

It is a non-corrosive product, so it is recommended on every traditional support used in building industry such as concrete, plaster, brickwork, copper, steel, aluminium, galvanized plate, glass, ceramic, wood, ABS, hard PVC, polycarbonate, polymethylmethacrylate, and varnished supports.

Compliant with ISO 11600-F&G-25LM regulations.

### APPLICATION FIELDS

Saratoga Neutral Silicone Sealant with Anti-mould protection is used for sealing sanitary and kitchen systems, bathrooms, shower glasses, washbasins, toilets, wash houses, whirlpool tubs, glasses and windows.

Saratoga Neutral Silicone Sealant with Anti-mould protection is ideal for expansion joints and connection between traditional façade elements, joints between walls and floors, staircases, prebuilt panels joints, separating walls joints, between window fixtures and brickworks, household electrical appliances, metallic carpentry, cars.

### APPLICATION

All surfaces must be compact, clean, dry, dust free and degreased.

- It is recommended to use a masking tape on both sides of the joint for a better result (remove right after application).
- Cut the nozzle at the desired diameter.
- Apply using a standard sealant gun or a compressed air one.
- Cannot be painted, therefore, paint before applying.
- Apply at the bottom of the gap some insulation material (such as adhesive tape); with deep gaps, fill with some fill-up material (such as Saratoga Joint•Filler or expanded plastic).

Clean surfaces and tools within 10 minutes with a clean cloth wetted with solvent or Saratoga Via•Sil Fresco. When cured, clean with Saratoga Via•Sil Indurito.

Specific data:		Transparent	White
Kind of sealant		Alcoxy	Alcoxy
Specific weight		1,01	1,51
Consistency		Thixotropic	Thixotropic
Extrusion rate	g/min.	15-25	15-25
Working time	minutes*	10	10
Cure time	mm/24h*	2	2
Application temperature	°C	+5 / +40	+5 / +40
Tensile strength	MPa	1,0	1,9
Modulus at 100% elongation	MPa	0,23	0,45
Elongation at break	%	500	700
Shore A hardness	°	10	20
Elastic recovery	%	>95	>90
Working movement	%	25	25
Heat resistance	°C	-50 / +180	-50 / +180

\*At 23°C and 50% relative humidity

### STORAGE AND SHELF LIFE

Between +20 and +25°C its shelf life is 12 months since manufacturing date.

### PRIMER

A primer is not needed on glass and ceramic, has excellent adhesion on the most common building industry materials.

For particular or exceptional adhesions, it is recommended to run some tests and, in case, use Saratoga Primer CLS with porous backings, or Saratoga Primer PM with metals and plastic materials.

### NOTE

Avoid contact with eyes and skin. Use only in a ventilate working environment.

## CAUTIONS

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site [www.saratoga.it](http://www.saratoga.it)

Product Description	Pack size	Product code	Box quantity	EAN Code
Transparent	280 g	85 154 001	30	8 005860 851542
Transparent	310 ml	85 125 001	30	8 005860 851252
White RAL 9010	390 g	85 152 001	30	8 005860 850026
WhiteRAL 9010	310 ml	85 122 001	30	8 005860 851221



12/2011, 3<sup>rd</sup> Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings . All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.