

## Saratoga Disotturante Chimico – Chemical Unclogger for Drain Pipes

Saratoga Disotturante Chimico – Chemical Unclogger for Drain Pipes is an oily sulphuric acid based liquid for treating clogged pipes.

### APPLICATION FIELDS

Saratoga Disotturante Chimico – Chemical Unclogger for Drain Pipes is the high concentration and rapid action professional treatment, that clears all clogged pipes from organic sediments and inerts (soaps, grease residues), from calcareous incrustations, hair, cellulose compounds, sanitary napkins, cigarettes, etc.

Acts on incrustations, without damaging plastic, iron and lead.

It can be used in sinks, wc, floor drains and drain pipes in general.

### APPLICATION AND INSTRUCTIONS

- Remove stagnant water.
- Wear suitable glasses and rubber gloves.
- To open, keep bottle in vertical, press down the safety cap and, at the same time, unscrew it.
- Pour slowly and with caution the product in the drain, using a plastic funnel, if possible.
- Close the bottle right after use.
- Let the product act for some minutes, ensure that it is completely drained, then let **cold water** flow a bit.
- Wait again for some minutes, and let **cold water** flow abundantly. If necessary, repeat the procedure.

During its action the product does not release gas or harmful fumes, but in specific conditions it can quickly develop acid water steam, therefore it is recommended to always work keeping the face back and wearing safety gloves and glasses.

Do not pour the Unclogger on water or other products (such as other uncloggers, soda or bleach) to avoid possible uncontrolled thermal reactions.

Do not use directly on aluminum, galvanized, tropicalized and chromed metals and magnesium; do not use on marble or every surface that is sensitive to acids. In these cases, guide the product to the drain with a funnel, avoiding that it could come in contact with those surfaces.

Do not use on damaged systems. For WC it is recommended to apply a rubber tube to the funnel to insert it to pass the gooseneck.

Specific data	
Appearance	Oily liquid
Colour	Dark amber
Smell	Odourless
Specific weight	1,818 – 1,850 g/l
Ideal yield	With sinks, showers and bidet, 200 ml abt
	With toilets and big drains, 300–400 ml abt
Cap	Safety child with seal

## STORAGE AND SHELF LIFE

Between +20 and +25°C its shelf life is 24 months since manufacturing date.

## CAUTIONS

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site [www.saratoga.it](http://www.saratoga.it)



01/03/2022, 2<sup>nd</sup> Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings . All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information. way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at