Saratoga Sforza®
Via Edison, 76 - 20090 Trezzano sul Naviglio (MILANO) - ITALY
TEL. +39.02.445731 - www.saratoga.it

Saratoga Fernovus Alte Temperature – High Temperatures

Saratoga Fernovus Alte Temperature – High Temperatures is an alkyl silicone resins and pigments resistant to temperatures up to +450°C based product.

APPLICATION FIELDS

Saratoga Fernovus Alte Temperature – High Temperatures can be applied as a single product in the protection of metal surfaces, both indoor and outdoor, that must endure high temperatures.

It is especially suitable for barbecues, exhaust pipes, boilers, ovens, fire screens, parts of stoves, mufflers, overheated steam pipes, manifolds, chimneys stacks, chimneys.

APPLICATION

- All surfaces must be clean, degreased, and dust free.
- Remove peeling surfaces and non-adherent or crumbly rust.
- Blend very well before use.
- Apply with brush or roll. Indoor application: one coat, outdoor: two coats; dry film thickness: 45-50 microns each coat.
- Can be applied directly on rusted surfaces, even if moistened, no need to sandpaper, nor to apply antirust or converters. Can be applied also on naked or varnished metal.
- To obtain a better and lasting result, it is necessary to expose the varnished parts, even once for a few minutes, to a temperature of at least +150°C (below which hardening and adhesion are partial).

Specific data	
Specific weight at +20°C	0,95-1,15 g/ml
VOC (ISO 11890-2)	525 g/l
Tack free	2-3 h
Fully dry	12-14 h
Minimum time between 1° and 2° coat	12 h
Krebs Stormer viscosity (ASTM D562)	105-115 K
Salt fog resistance (ASTM B117)	>200 h
Adhesion to support (ASTM D3359)	100%
Continue temperature resistance	+250-300°C
Temperature resistance (peaks)	Up to +450°C
Yield for coat	abt. 4 m^2/l

STORAGE AND SHELF LIFE

In unopened original packaging, between +20 and +25°C.

CAUTIONS

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Box quantity	EAN Code
Aluminium	250 ml	88 645 001	6	8 005860 886452
Black	250 ml	88 645 002	6	8 005860 990081



02/17/2020, 2nd Rev- *The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings . All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.*