

Saratoga low noise PPL Technical Data Sheet

Saratoga low noise PPL Tape is a low noise unrolling self-adhesive tape with polypropylene and acrylic adhesive support, in water dispersion.

APPLICATION FIELDS

Ideal for closing all kind of boxes, packages, envelopes, etc. recommended for room temperature applications. Solvent free, extremely resistant to ageing caused by light sources, keeping unchanged its functionality as time goes by.

Specific data	
Colour	Havana/White/Transparent
Support thickness	28µ ±10%
Total thickness	46µ ±10%
Adhesion	2,9 N/cm ±10%
Elongation at break	145% +20%
Breaking load	43 N/cm ±10%
Smell	Typical
Density	0,9-1,2
Solubility in water	Insoluble

STORAGE AND SHELF LIFE

In unopened original packaging, between +15 and +25°C its shelf life is 12 months since manufacturing date. In case of storage with different temperatures, restore the tape back to the above-mentioned ones before using it.

Keep in a dry place, out of the light, protect from frost and from direct heat sources; do not keep on the ground. In case of low temperatures unrolling is noisier than usual. As time goes by the tape increases its feature of low noise unrolling.

CAUTIONS

Keep out of the reach of children.

Avoid contact with eyes, mouth and hair.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Box quantity	EAN Code
Roll mm 50 Havana	50 m	63 009 050	72	8 005860 630093
Roll mm 15 Havana	66 m	63 010 020	72	8 005860 630109
Roll mm 50 Havana	132 m	63 018 001	36	8 005860 630185
Roll mm 50 White	66 m	63 010 021	72	8 005860 990265
Roll mm 50 Transparent	66 m	63 010 025	72	8 005860 990272
Roll mm 50 Transparent	132 m	63 018 002	36	8 005860 899193

