

Saratoga Smalto Acrilico PROF

Saratoga Smalto Acrilico PROF: acrylic paint, fast drying spray for professional users. Bright enamel, available in a wide range of RAL colours.

APPLICATION FIELDS

Saratoga Smalto Acrilico PROF has excellent adhesion characteristics and is suitable for painting on many different materials such as: wood, metal, glass, ceramics, plaster, masonry, some plastics (ABS, PVC, rigid polystyrene and methacrylate).

High coverage, high durability, UV-resistant, is free from lead and chlorofluorocarbons, is very bright and can be painted over.

APPLICATION

- Carefully clean the surface from grease, dust, water, etc.
- Shake can for a long time, until hearing for a minute the sound of the marbles inside the can.
- Keeping the can 30 cm from the surface to treat, apply with slight coats. For a better result, cross horizontal coats with vertical ones (after about a minute).
- With self-cleaning valve.

For a better result, sand the part to treat with thin sandpaper (wet n° 400)

Clean varnish with Acetone and/or Nitro Diluent.

Specific data	
Appearance	Can containing liquid under pressure
Density at 20°C	0,75-0,8 g/ml
Yield	1,5-2 mq
Temperature resistance	120°C
Coats needed:	1 in internals
	2-3 in externals
Skin formation time	15-20 minutes
Fully dry	24 hours

*according to humidity and application temperature.

It is recommended to use the can at +20°C or bringing its temperature to +20°C before applying.

With childproof patented safety cap and colour reference token on cap.

STORAGE AND SHELF LIFE

In unopened original packaging, between +20 and +25°C. In any case, temperature must be over +5°C and keep out of sunlight.

CAUTIONS

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Box quantity
Can, Different colours	400 ml	88 300 - - -	6

