Via Edison, 76 - 20090 Trezzano sul Naviglio (MILANO) - ITALY TEL. +39.02.445731 - www.saratoga.it

Saratoga U.S.A. White Neutro Lamiere Silicone Sealant Technical Data Sheet

Saratoga U.S.A. White Neutro Lamiere is a high quality neutral one-component silicone sealant.

APPLICATION FIELDS

It is used in guttering, to seal eaves and drainpipes, to seal metal coverings, between metal sheets or plates and walls, flashings, metal carpentry, insulation and air-conditioning. It has excellent adhesion to galvanized, pre-varnished and stainless plate, iron, copper, aluminium, tinplate, bronze, brass, lead and porous surfaces.

APPLICATION

- · All surfaces must be clean and dry.
- Prepare the surface to treat and apply a masking tape on both sides of the joint for a better result (remove right after application).
- Cut the nozzle at the desired diameter.
- Apply using a standard sealant gun or a compressed air one.
- · Cannot be painted, therefore, paint before applying.

Clean within 10 minutes with a clean cloth wetted with solvent. When cured, clean with Saratoga Via Sil Indurito.

| Specific data | | | | |
|-------------------------|---------------|--|--|--|
| Kind of sealant | Alcoxy | | | |
| Specific weight | 1,52 | | | |
| Consistency | Thixotropic | | | |
| Extrusion rate | 15-25 g/min | | | |
| Working time | 10 min | | | |
| Cure time | 2-3 mm/24 h | | | |
| Application temperature | +5/+40 °C | | | |
| Working movement | 25 % | | | |
| Temperature resistance | -50 / +150 °C | | | |
| Elongation at break | >450 % | | | |
| Elastic recovery | >90 % | | | |

^{*}At 23°C and 50% relative humidity

STORAGE AND SHELF LIFE

Between +20 and +25°C its shelf life is 12 months since manufacturing date.

CAUTIONS

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

| Product Description | Pack size | Product code | Box quantity | EAN Code |
|----------------------------|------------------|--------------|--------------|-----------------|
| Gray | 280 ml cartridge | 85 414 010 | 15 | 8 005860 996885 |
| Copper | 280 ml cartridge | 85 414 011 | 15 | 8 005860 990234 |
| Dark brown | 280 ml cartridge | 85 414 012 | 15 | 8 005860 990241 |



07/21/2016, 1st Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.