

Saratoga Happy Color Primer

Saratoga Happy Color Primer is the transparent undercoat to apply before normal varnishing, to ensure excellent adhesion of any spray enamel on difficult surfaces, such as plastics, metal alloys and metals in general, which otherwise would not be paintable.

APPLICATION FIELDS

Saratoga Acrylic Happy Color Primer is suitable for plastic surfaces (ABS, methacrylate, polycarbonate, hard PVC), car bumpers, motorcycles casings, miniatures in general, metal surfaces and alloys.

APPLICATION

- All surfaces must be dust free, clean, dry and degreased.
- Shake can until hearing for a minute the sound of the marbles inside the can.
- Keeping the can 20-30 cm from the surface to treat, apply slowly with slight crossed coats.
- Wait at least an hour before proceeding with following applications.

Clean varnish with Acetone and/or Nitro Diluent.
With self-cleaning valve.

Specific data		
Appearance		Can containing liquid under pressure
Colour		Colourless
Odour		Typical of solvent
Density at 20°C	g/ml	0,75-0,80
Pressure at 20°C	bar	4 ± 0,5
Brightness-Gloss degree	Gloss	25
Skin formation time	minutes	10
Tack free	minutes	15-20
Fully dry	hours	24

STORAGE AND SHELF LIFE

In unopened original packaging, between +20 and +25°C.

CAUTIONS

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Box quantity	EAN code
Can	400 ml	88 169 001	6	8 005860 881693

