

Saratoga Super-Active Paint Remover Technical Data Sheet

Saratoga Super-Active Paint Remover is a paint stripper made of oxygenated solvents (without chlorinate) with deeply effects.

APPLICATION FIELDS

It acts deep down, rapidly eliminating every type of paint, even the oldest and most resistant coatings (with the exception of two-component products) from wood, iron and non-ferrous metal.

It does not alter the surfaces on which it is applied, does not blacken wood and delays the onset of rust on metallic surfaces treated (be careful not to apply the product on plastic surfaces).

Its gel formula allows vertical applications without running, for faster and more precise work.

Effective on undercoats, impregnating agents, anti-rust coatings, synthetic paints, oil paints, nitrocellulose, acrylic, and polyurethane paints, standard enamels and stoving enamels, water paints, wall plastics and also on plaster, adhesives for carpets, parquets and paints used on boats.

APPLICATION

- On the surface where paint is to be removed, spread out with a brush a uniform coat of the product 2-3 mm thick, bearing in mind that application on flat surfaces allows a faster and better result (do not apply on hot surfaces or surfaces exposed to direct sunlight).
- Wait from 3-5 minutes to 4 hours, depending on the type and layers of paint to remove (the product remains active until it dries, up to 24 hours).
- As a rough guide, 20-30 minutes are needed for synthetic paints and water-based coatings, 1-2 hours for solvent-based or water-based polyurethane paints, and 4 hours for polyester paints and stoving coating.
- Remove softened layers with a metallic spatula or scraper (on wooden surfaces it is advisable to use the spatula or scraper only in the direction of the veins of the wood).
- Rinse with lukewarm water and clean using a brush with hard bristles (natural or synthetic).
- Wait 24 hours before proceeding with the application of the new coating layer.
- In case there are more layers to be removed, it is possible to repeat the removing process more than once.

Specific data	
Appearance	Gel
Colour	Colorless
Density at 15°C	0,925 + 0,007

STORAGE AND SHELF LIFE

In unopened original packaging, between +20 and +25°C.

CAUTIONS

Keep in a cool place.

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Box quantity	EAN code
Tin	750 ml	54 293 001	6	8 005860 542938



08/30/2022 , 3rd Rev. - The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings . All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.