

Saratoga Newstick Top

Saratoga Newstick Top is the one-component polychloroprene solvent based adhesive, very clear, with exceptional cohesion strength, for a universal use.

APPLICATION FIELDS

Contact adhesive for general purposes. Ideal for bonding plastic laminates, cork, carpeting, cloths, rubber, hides, leather, felts, veneers, hard PVC and cardboard between themselves and with hard surfaces such as wood, metal sheets, glass, chipboard, concrete and other supports.

APPLICATION AND INSTRUCTIONS

- Make sure that the surfaces to glue are clean, dry, degreased (in case wash with a suitable degreaser) and solvent free.
- Apply a thin coat of adhesive on both surfaces (spread an enough and uniform quantity of product).
- Wait for about 10-20 minutes for the solvent to evaporate, according to room temperature.
- Join the two surfaces pressing with the maximum possible strength for a few seconds. The strength, not the duration of the pressure is important.

Clean with acetone.

It is necessary that the spread surfaces are free from traces of solvent before assembly, above all in case of bonding non-absorbing materials; otherwise undesirable bubbles that would compromise bonding grip could grow up.

Specific data	
Aspect	Pale yellow fluid
Viscosity	2200 – 2800 mPas
Dry residue	21,0 – 24,0%
Application temperature	+5 / +35°C

STORAGE AND SHELF LIFE

Between +20 and +25°C. Store in a cool, ventilated and dry place. Keep out of sun or heat sources. Too low temperatures (lower than 0°C) could increase viscosity with subsequent difficulty to spread it, while too high temperatures (above 30°C) could produce overpressure within the packaging.

CAUTIONS

Keep out of the reach of children. Work in a ventilated environment.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Box quantity	EAN Code
Newstick Top Tube	18 g	57 170 003	30	8 005860 899810
Newstick Top Tube	50 g	57 171 002	25	8 005860 899827
Newstick Top Tube	125 g	57 172 002	25	8 005860 899803

