

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 1 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code: 54145001_SVAP L/ETICHETTE 200ML
Product name: SVAP LEVAETICHETTE SPRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use: LABEL REMOVER

Identified Uses	Industrial.	Professional.	Consumer.
GENERAL USE	-	-	✓
INDUSTRIAL MAINTENANCE	✓	✓	-

Uses advised against: This product is not recommended for all those uses not specifically identified on the label.

1.3. Details of the supplier of the safety data sheet.

Name: Saratoga Int. Sforza S.p.A.
Full address: Via Edison 76
District and Country: 20090 Trezzano s/Naviglio (MILAN)
ITALY
Tel. 0039.02.445731
Fax. 0039.02.4452742

e-mail address of the competent person.
responsible for the Safety Data Sheet. trading@saratogasforza.com

1.4. Emergency telephone number.

For urgent inquiries refer to.
CAV - Ospedale Pediatrico "Bambino Gesù" - Roma - Tel. +39 06 68593726 (h24)
CAV - Azienda Ospedaliero-Universitaria Foggia - Foggia - Tel. +39 0881 732326 (h24)
CAV - Azienda Ospedaliera "A. Cardarelli" - Napoli - Tel. +39 081 7472870 (h24)
CAV - Policlinico "Umberto I" - Roma - Tel. +39 06 4450618 (h24)
CAV - Policlinico "A. Gemelli" - Roma - Tel. +39 06 3054343 (h24)
CAV - Azienda Ospedaliera "Careggi" U.O. Tossicologia Medica - Firenze - Tel. +39 055 7947819(h24)
CAV - Centro Nazionale di Informazione Tossicologica - Pavia - Tel. +39 0382 24444 (h24)
CAV - Ospedale "Niguarda Ca' Granda" - Milano - Tel. +39 02 66101029 (h24)
CAV - Azienda Ospedaliera "Papa Giovanni XXIII" - Bergamo - Tel. +39 800 883300 (h24)

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 2 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames or other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurised container: Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye and face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P501	Dispose of contents and container to authorized collection centers.

Contains: DIPENTENE

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 3 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

SECTION 3. Composition/information on ingredients.

3.2. Mixtures.

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification.

Classification 1272/2008 (CLP).

PROPANE

CAS. 74-98-6

$15 \leq x < 30$

Flam. Gas 1 H220, Note U

EC. 200-827-9

INDEX. 601-003-00-5

Reg. no. 01-2119486944-21-xxxx

BUTANE

CAS. 106-97-8

$5 \leq x < 15$

Flam. Gas 1 H220, Note C U

EC. 203-448-7

INDEX. 601-004-00-0

Reg. no. 01-2119474691-32-xxxx

XYLENE (MIXTURE OF ISOMERS)

CAS. 1330-20-7

$5 \leq x < 10$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Note C

EC. 215-535-7

INDEX. 601-022-00-9

Reg. no. 01-2119488216-32

ETHANOL

CAS. 64-17-5

$1 \leq x < 5$

Flam. Liq. 2 H225

EC. 200-578-6

INDEX. 603-002-00-5

Reg. no. 01-2119457610-43

ETHYL ACETATE

CAS. 141-78-6

$1 \leq x < 5$

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC. 205-500-4

INDEX. 607-022-00-5

Reg. no. 01-2119475103-46

METHYLAL

CAS. 109-87-5

$1 \leq x < 5$

Flam. Liq. 2 H225

EC. 203-714-2

INDEX. -

Reg. no. 01-2119664781-31-xxxx

Isobutane

CAS. 75-28-5

$1 \leq x < 5$

Flam. Gas 1 H220, Note C U

EC. 200-857-2

INDEX. 601-004-00-0

Reg. no. 01-2119485395-27-xxxx

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 4 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

1,3-Dioxolane

CAS. 646-06-0

$1 \leq x < 5$

Flam. Liq. 2 H225, Eye Irrit. 2 H319

EC. 211-463-5

INDEX. 605-017-00-2

Reg. no. 01-2119490744-29-0001

DIPENTENE

CAS. 138-86-3

$0,25 \leq x < 1$

Flam. Liq. 3 H226, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic
Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1, EUH208, Note C

EC. 205-341-0

INDEX. 601-029-00-7

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 36,80 %

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown.
For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 5 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions.

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 6 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2016

PROPANE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	1800	1000	7200	4000
MAK	DEU	1800	1000	7200	4000
TLV	GRC	1800	1000		
TLV-ACGIH			1000		

BUTANE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	2400	1000	9600	4000

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 7 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

MAK	DEU	2400	1000	9600	4000
VLA	ESP		800		
VLEP	FRA	1900	800		
WEL	GBR	1450	600	1810	750
TLV	GRC	2350	1000		
TLV-ACGIH				2377	1000

XYLENE (MIXTURE OF ISOMERS)

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN.
MAK	DEU	440	100	880	200	SKIN.
VLA	ESP	221	50	442	100	SKIN.
VLEP	FRA	221	50	442	100	SKIN.
WEL	GBR	220	50	441	100	
TLV	GRC	435	100	650	150	
VLEP	ITA	221	50	442	100	SKIN.
VLE	PRT	221	50	442	100	SKIN.
OEL	EU	221	50	442	100	SKIN.
TLV-ACGIH		434	100	651	150	

ETHANOL

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	960	500	1920	1000	
MAK	DEU	960	500	1920	1000	
VLA	ESP			1910	1000	
VLEP	FRA	1900	1000	9500	5000	
WEL	GBR	1920	1000			
TLV	GRC	1900	1000			
TLV-ACGIH				1884	1000	

ETHYL ACETATE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1500	400	3000	800	
MAK	DEU	1500	400	3000	800	
VLA	ESP	1460	400			
VLEP	FRA	1400	400			
WEL	GBR		200		400	
TLV	GRC	1400	400			

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 8 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

TLV-ACGIH 1441 400

METHYLAL

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	3200	1000	6400	2000
MAK	DEU	3200	1000	6400	2000
VLA	ESP	3165	1000		
VLEP	FRA	3100	1000		
WEL	GBR	3160	1000	3950	1250
TLV-ACGIH		3112	1000		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION
None required.

SKIN PROTECTION
Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION
Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION
If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).
Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 9 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

Appearance	aerosol
Colour	milky
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	< -5 °C.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	Not available.
Evaporation Rate	Not available.
Flammability of solids and gases	flammable gas
Lower inflammability limit.	Not applicable.
Upper inflammability limit.	Not applicable.
Lower explosive limit.	Not applicable.
Upper explosive limit.	Not applicable.
Vapour pressure.	4750 mmHg
Vapour density	< 1 (Aria =1)
Relative density.	0,71
Solubility	partially soluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	> 270 °C.
Decomposition temperature.	Non definita
Viscosity	> 19cSt 1 15°C
Explosive properties	not applicable
Oxidising properties	not applicable

9.2. Other information.

Total solids (250°C / 482°F)	0,80 %
VOC (Directive 2010/75/EC) :	99,50 % - 696,50 g/litre.
VOC (volatile carbon) :	40,49 % - 287,48 g/litre.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY

cod. 54145001

Revision: 13 / EN

Page 10 of 17

Date of print: 02/08/2019

Date of review: 18/06/2018

XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

ETHANOL

Risk of explosion on contact with: alkaline metals, alkaline oxides, calcium hypochlorite, sulphur monofluoride, acetic anhydride, acids, concentrated hydrogen peroxide, perchlorates, perchloric acid, perchloronitrile, mercury nitrate, nitric acid, silver, silver nitrate, ammonia, silver oxide, ammonia, strong oxidising agents, nitrogen dioxide. May react dangerously with: bromoacetylene, chlorine acetylene, bromine trifluoride, chromium trioxide, chromyl chloride, fluorine, potassium tert-butoxide, lithium hydride, phosphorus trioxide, black platinum, zirconium (IV) chloride, zirconium (IV) iodide. Forms explosive mixtures with: air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

10.4. Conditions to avoid.

Avoid overheating.

ETHANOL

Avoid exposure to: sources of heat, naked flames.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, aluminium, nitrates, chlorosulphuric acid. Incompatible materials: plastic materials.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

XYLENE (MIXTURE OF ISOMERS) Has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 11 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:> 20 mg/l
LC50 (Inhalation - mists / powders) of the mixture:Not classified (no significant component).
LD50 (Oral) of the mixture:Not classified (no significant component).
LD50 (Dermal) of the mixture:>2000 mg/kg

1,3-Dioxolane
LD50 (Oral).> 2000 mg/kg
LD50 (Dermal).> 15000 mg/kg
LC50 (Inhalation).> 68,4 mg/kg

XYLENE (MIXTURE OF ISOMERS)
LD50 (Oral).3523 mg/kg Rat
LD50 (Dermal).4350 mg/kg Rabbit
LC50 (Inhalation).26 mg/l/4h Rat

METHYLAL
LD50 (Oral).6453 mg/kg Rat - Wistar
LD50 (Dermal).> 5000 mg/kg Rabbit - New Zeland white
LC50 (Inhalation).57 mg/l Mouse - Swiss

ETHANOL
LD50 (Oral).> 5000 mg/kg Rat
LC50 (Inhalation).120 mg/l/4h Pimephales promelas

SKIN CORROSION / IRRITATION.

Causes skin irritation.

SERIOUS EYE DAMAGE / IRRITATION.

Causes serious eye irritation.

RESPIRATORY OR SKIN SENSITISATION.

Sensitising for the skin.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth.

SECTION 12. Ecological information.

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity.

1,3-Dioxolane

LC50 - for Fish. > 100 mg/l/96h

EC50 - for Crustacea. > 772 mg/l/48h

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 12 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

METHYLAL

LC50 - for Fish.	> 1000 mg/l/96h Danio rerio
EC50 - for Crustacea.	> 1000 mg/l/48h Daphnia magna

DIPENTENE

LC50 - for Fish.	80 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea.	17 mg/l/48h Daphnia magna

12.2. Persistence and degradability.

XYLENE (MIXTURE OF ISOMERS)

Solubility in water.	100 - 1000 mg/l
----------------------	-----------------

Biodegradability: Information not available.

METHYLAL

Solubility in water.	> 10000 mg/l
----------------------	--------------

NOT rapidly biodegradable.

BUTANE

Solubility in water.	0,1 - 100 mg/l
----------------------	----------------

Rapidly biodegradable.

PROPANE

Solubility in water.	0,1 - 100 mg/l
----------------------	----------------

Rapidly biodegradable.

DIPENTENE

NOT rapidly biodegradable.

ETHANOL

Solubility in water.	1000 - 10000 mg/l
----------------------	-------------------

Rapidly biodegradable.

ETHYL ACETATE

Solubility in water.	> 10000 mg/l
----------------------	--------------

Rapidly biodegradable.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 13 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

12.3. Bioaccumulative potential.

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water.	3,12
BCF.	25,9

METHYLAL

Partition coefficient: n-octanol/water.	0,18
BCF.	0,6

BUTANE

Partition coefficient: n-octanol/water.	1,09
---	------

PROPANE

Partition coefficient: n-octanol/water.	1,09
---	------

DIPENTENE

Partition coefficient: n-octanol/water.	4,5
---	-----

ETHANOL

Partition coefficient: n-octanol/water.	-0,35
---	-------

ETHYL ACETATE

Partition coefficient: n-octanol/water.	0,68
BCF.	30

12.4. Mobility in soil.

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water.	2,73
------------------------------------	------

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 14 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name.

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS,
FLAMMABLE

14.3. Transport hazard class(es).

ADR / RID:	Class: 2	Label: 2.1
IMDG:	Class: 2	Label: 2.1
IATA:	Class: 2	Label: 2.1



14.4. Packing group.

ADR / RID, IMDG, -
IATA:

14.5. Environmental hazards.

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 15 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special Provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 100 Kg	Packaging instructions: 130
	Pass.:	Maximum quantity: 25 Kg	Packaging instructions: 130
	Special Instructions:	A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.
Point. 40

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY
cod. 54145001
Revision: 13 / EN

Page 16 of 17

Date of print: 02/08/2019
Date of review: 18/06/2018

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains <name of sensitising substance>. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SVAP LEVAETICHETTE SPRAY

cod. 54145001

Revision: 13 / EN

Page 17 of 17

Date of print: 02/08/2019

Date of review: 18/06/2018

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

03.