

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 1 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code: 54265001
Product name: SILICONE DISTACCANTE 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use: SILICON RELEASE AGENT FOR INDUSTRIAL USE.
Uses advised against: This product is not recommended for all those industrial, professional or consumer uses not specifically identified on the label.

Identified Uses	Industrial.	Professional.	Consumer.
GENERAL USE	-	-	✓
INDUSTRIAL MAINTENANCE	✓	✓	-

1.3. Details of the supplier of the safety data sheet.

Name: SARATOGA INT. SFORZA SPA
Full address: VIA EDISON, 76
District and Country: 20090 TREZZANO SUL NAGIVLIO (MILAN)
ITALY
Tel. 0039.02.445731
Fax. 0039.02.4452742

e-mail address of the competent person.

responsible for the Safety Data Sheet: trading@saratogasforza.com
Product distribution by: SARATOGA INT. SFORZA SPA

1.4. Emergency telephone number.

For urgent inquiries refer to.

CAV - Ospedale Pediatrico "Bambino Gesù" - Roma - Tel. +39 06 68593726 (h24)
CAV - Azienda Ospedaliero-Universitaria Foggia - Foggia - Tel. +39 0881 732326 (h24)
CAV - Azienda Ospedaliera "A. Cardarelli" - Napoli - Tel. +39 081 7472870 (h24)
CAV - Policlinico "Umberto I" - Roma - Tel. +39 06 4450618 (h24)
CAV - Policlinico "A. Gemelli" - Roma - Tel. +39 06 3054343 (h24)
CAV - Azienda Ospedaliera "Careggi" U.O. Tossicologia Medica - Firenze - Tel. +39 055 7947819(h24)
CAV - Centro Nazionale di Informazione Tossicologica - Pavia - Tel. +39 0382 24444 (h24)
CAV - Ospedale "Niguarda Ca' Granda" - Milano - Tel. +39 02 66101029 (h24)
CAV - Azienda Ospedaliera "Papa Giovanni XXIII" - Bergamo - Tel. +39 800 883300 (h24)

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 2 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

Hazard classification and indication:

Aerosol, category 1

H222

H229

Extremely flammable aerosol.

Pressurised container: may burst if heated.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H222

Extremely flammable aerosol.

H229

Pressurised container: may burst if heated.

Precautionary statements:

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P210

Keep away from heat / sparks / open flames / hot surfaces. No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Pressurized container: Do not pierce or burn, even after use.

P271

Use only outdoors or in a well-ventilated area.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P501

Dispose of contents/container to authorized collection centers.

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.2. Mixtures.

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification.

Classification 1272/2008 (CLP).

BUTANE

CAS. 106-97-8

50 ≤ x < 75

Flam. Gas 1 H220, Note C U

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 3 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

EC. 203-448-7

INDEX. 601-004-00-0

Reg. no. 01-2119474691-32-xxxx

PROPANE

CAS. 74-98-6

$30 \leq x < 50$

Flam. Gas 1 H220, Note U

EC. 200-827-9

INDEX. 601-003-00-5

Reg. no. 01-2119486944-21-xxxx

DIMETHYLETHER

CAS. 115-10-6

$5 \leq x < 15$

Flam. Gas 1 H220, Note P

EC. 204-065-8

INDEX. 603-019-00-8

Reg. no. 01-2119472128-37-xxxx

IsoBUTANE

CAS. 75-28-5

$1 \leq x < 5$

Flam. Gas 1 H220, Note C

EC. 200-857-2

INDEX. 601-004-00-0

Reg. no. 01-2119485395-27-xxxx

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 83,40 %

SECTION 4. First aid measures.

4.1. Description of first aid measures.

No episodes of harm to the staff authorised to use the product have been reported. The following general measures should be adopted as necessary:
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.
INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Do not give anything by mouth to an unconscious person.
EYES and SKIN: Wash with plenty of water. In the event of persistent irritation, get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed.

No episodes of damage to health ascribable to the product have been reported.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 4 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions.

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 5 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

Storage class TRGS 510 (Germany):

2B

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
	TLV-ACGIH	ACGIH 2016

BUTANE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
VLA	ESP		800		
VLEP	FRA	1900	800		
WEL	GBR	1450	600	1810	750
TLV	GRC	2350	1000		
TLV-ACGIH				2377	1000

PROPANE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML
54265001

Version: 13 / EN

Page 6 of 13

Print date: 13.11.2018
Revision date: 28.09.2016

AGW	DEU	1800	1000	7200	4000
MAK	DEU	1800	1000	7200	4000
TLV	GRC	1800	1000		
TLV-ACGIH			1000		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	aerosol
Colour	transparent
Odour	imperceptible
Odour threshold.	Not Defined
pH.	Not applicable.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	Not available.
Evaporation Rate	Not Defined
Flammability of solids and gases	flammable gas
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	2,8 % (V/V).
Upper explosive limit.	9,2 % (V/V).

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 7 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

Vapour pressure.	1575 mmHg
Vapour density	< 1(Aria =1)
Relative density.	Non Definita
Solubility	soluble in organic solvents
Partition coefficient: n-octanol/water	Non Definito
Auto-ignition temperature.	> 270 °C.
Decomposition temperature.	Non Definita
Viscosity	> 100 cSt a 40°C
Explosive properties	not applicable
Oxidising properties	not applicable

9.2. Other information.

Total solids (250°C / 482°F)	10,94 %
VOC (Directive 2010/75/EC) :	93,40 % - 560,40 g/litre.
VOC (volatile carbon) :	0

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

Avoid overheating.

10.5. Incompatible materials.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 8 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component).
LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component).
LD50 (Oral) of the mixture: Not classified (no significant component).
LD50 (Dermal) of the mixture: Not classified (no significant component).

Dimethylether
LC50 (Inhalation). > 309018 mg/m³

SKIN CORROSION / IRRITATION.

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION.

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth.

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity.

Dimethylether

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 9 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

LC50 - for Fish. > 4001 mg/l/96h

12.2. Persistence and degradability.

Dimethylether

Entirely biodegradable.

BUTANE

Solubility in water. 0,1 - 100 mg/l

Rapidly biodegradable.

PROPANE

Solubility in water. 0,1 - 100 mg/l

Rapidly biodegradable.

12.3. Bioaccumulative potential.

BUTANE

Partition coefficient: n-octanol/water. 1,09

PROPANE

Partition coefficient: n-octanol/water. 1,09

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 10 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name.

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS,
FLAMMABLE

14.3. Transport hazard class(es).

ADR / RID:	Class: 2	Label: 2.1
IMDG:	Class: 2	Label: 2.1
IATA:	Class: 2	Label: 2.1



14.4. Packing group.

ADR / RID, IMDG, -
IATA:

14.5. Environmental hazards.

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user.

ADR / RID:	HIN - Kemler: -- Special Provision: -	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 100 Kg	Packaging instructions: 130
	Pass.:	Maximum quantity: 25 Kg	Packaging instructions: 130

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 11 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

Special Instructions:

A802

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product

Point. 40

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

WGK 0: Not hazardous to waters

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 12 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

SAFETY DATA SHEET
in accordance with Regulation (CE) Num. 1907/2006 (REACH)

SILICONE DISTACCANTE 400ML

54265001

Version: 13 / EN

Page 13 of 13

Print date: 13.11.2018

Revision date: 28.09.2016

- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01.