

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 1 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

---

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

---

### 1.1 Product identifier

**Product name:** EDD SILICONE ACETICO TRASPARENTE AU11 cod.85551001

**Identified uses:** Acetoxy silicone sealant

**Uses advised against:** This product is not recommended for all those uses not specifically identified on the label.

### 1.3 Details of the supplier of the safety data sheet

#### COMPANY IDENTIFICATION

Saratoga Int. Sforza Spa

Via Edison 76

20090 Trezzano s/Naviglio (MI)

Tel. +039 02.445731 Fax +039 02.4452742

trading@saratogasforza.com

### 1.4 EMERGENCY TELEPHONE NUMBER

SARATOGA INT. SFORZA SPA + 039 02 445731 from Monday to Friday  
(h.09:00-13:00 / 14:00-17:30)

---

## SECTION 2: HAZARDS IDENTIFICATION

---

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008:

Long-term (chronic) aquatic hazard - Category 3 - H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

**SAFETY DATA SHEET**

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11  
cod.85551001  
Versione: 7.1/ EN

Pag. 2 di 27

Print Date: 06/04/2023  
Revision Date: 06/04/2023

**Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P102 Keep out of reach of children.  
P262 Avoid contact with the eyes and the skin.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P501 Dispose of the contents and the container in authorized collection centers.

**Supplemental information**

EUH208 Contains: 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one; Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane. May produce an allergic reaction.

**2.3 Other hazards**

This product contains octamethylcyclotetrasiloxane (D4) that has been identified by the Member State Committee of ECHA as fulfilling the PBT and vPvB criteria laid down in Annex XIII to Regulation (EC) No 1907/2006. See Section 12 for additional information.

**Endocrine disrupting properties**

Environment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Human Health: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical nature:** Silicone elastomer

**3.2 Mixtures**

This product is a mixture.

| CASRN /<br>EC-No. /<br>Index-No.                                                             | REACH<br>Registration<br>Number | Concentration       | Component                                                                         | Classification:<br>REGULATION (EC) No<br>1272/2008                                                                                                                                                                   |
|----------------------------------------------------------------------------------------------|---------------------------------|---------------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>CASRN</b><br>64742-47-8<br><b>EC-No.</b><br>265-149-8<br><b>Index-No.</b><br>649-422-00-2 | 01-2119484819-18                | >= 10,0 - <= 17,0 % | Distillates<br>(petroleum), hydro-<br>treated light;<br>Kerosine —<br>unspecified | Flam. Liq. 3; H226<br>Asp. Tox. 1; H304<br><br>Acute toxicity estimate<br>Acute oral toxicity:<br>> 5 000 mg/kg<br>Acute inhalation toxicity:<br>> 5 mg/l, 8 Hour, vapour<br>Acute dermal toxicity:<br>> 5 000 mg/kg |
| <b>CASRN</b><br>64742-46-7                                                                   | —                               | >= 10,0 - <= 17,0 % | Distillates<br>(petroleum),                                                       | Asp. Tox. 1; H304                                                                                                                                                                                                    |

# SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 3 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

|                                                                                              |   |                       |                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------------------------------------------------------------------|---|-----------------------|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EC-No.</b><br>265-148-2<br><b>Index-No.</b><br>649-221-00-X                               |   |                       | hydrotreated middle; Gasoil — unspecified   | Acute toxicity estimate<br>Acute oral toxicity:<br>> 5 000 mg/kg<br>Acute inhalation toxicity:<br>> 5,2 mg/l, 4 Hour, dust/mist<br>Acute dermal toxicity:<br>> 3 160 mg/kg                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>CASRN</b><br>556-67-2<br><b>EC-No.</b><br>209-136-7<br><b>Index-No.</b><br>014-018-00-1   | — | >= 0,013 - <= 0,051 % | octamethylcyclotetrasiloxane                | Flam. Liq. 3; H226<br>Repr. 2; H361f<br>Aquatic Chronic 1; H410<br><br>M-Factor (Chronic aquatic toxicity): 10<br><br>Acute toxicity estimate<br>Acute oral toxicity:<br>> 4 800 mg/kg<br>Acute inhalation toxicity:<br>36 mg/l, 4 Hour, dust/mist<br>Acute dermal toxicity:<br>> 2 400 mg/kg                                                                                                                                                                                                                                                                                                                   |
| <b>CASRN</b><br>64359-81-5<br><b>EC-No.</b><br>264-843-8<br><b>Index-No.</b><br>613-335-00-8 | — | <= 0,0015 %           | 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one | Acute Tox. 4; H302<br>Acute Tox. 2; H330<br>Skin Corr. 1; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>STOT SE 3; H335<br>(Respiratory system)<br>Aquatic Acute 1; H400<br>Aquatic Chronic 1; H410<br><br>M-Factor (Acute aquatic toxicity): 100<br>M-Factor (Chronic aquatic toxicity): 100<br><br>specific concentration limit<br>Skin Sens. 1A; H317<br>>= 0,0015 %<br>Skin Irrit. 2; H315<br>0,025 - < 5 %<br>Eye Irrit. 2; H319<br>0,025 - < 3 %<br><br>Acute toxicity estimate<br>Acute oral toxicity:<br>567 mg/kg<br>Acute inhalation toxicity:<br>0,16 mg/l, dust/mist<br>Acute dermal toxicity: |

**SAFETY DATA SHEET**  
**According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH**

EDD SILICONE ACETICO TRASPARENTE AU11  
cod.85551001  
Versione: 7.1/ EN

Pag. 4 di 27

Print Date: 06/04/2023  
Revision Date: 06/04/2023

|                                                                                   |                  |                         |                                                          |                                                                                                                                                                                                            |
|-----------------------------------------------------------------------------------|------------------|-------------------------|----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                   |                  |                         |                                                          | > 2 000 mg/kg                                                                                                                                                                                              |
| <b>CASRN</b><br>68928-76-7<br><b>EC-No.</b><br>273-028-6<br><b>Index-No.</b><br>— | 01-2120770324-57 | >= 0,008 - <= 0,02<br>% | Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane | Acute Tox. 4; H302<br>Skin Irrit. 2; H315<br>Skin Sens. 1A; H317<br>Aquatic Chronic 3; H412<br><br>Acute toxicity estimate<br>Acute oral toxicity:<br>892 mg/kg<br>Acute dermal toxicity:<br>> 2 000 mg/kg |

For the full text of the H-Statements mentioned in this Section, see Section 16.

*Note*

4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one:

The toxic by inhalation classification of the substance does not apply to non-inhalable mixtures.

---

## SECTION 4: FIRST AID MEASURES

---

### 4.1 Description of first aid measures

**General advice:**

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**Skin contact:** Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation or rash occurs. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

**Ingestion:** Rinse mouth with water. No emergency medical treatment necessary.

### 4.2 Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

### 4.3 Indication of any immediate medical attention and special treatment needed

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 5 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

**Notes to physician:** Maintain adequate ventilation and oxygenation of the patient. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

---

## SECTION 5: FIREFIGHTING MEASURES

---

### 5.1 Extinguishing media

**Suitable extinguishing media:** Water spray. Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical.

**Unsuitable extinguishing media:** None known..

### 5.2 Special hazards arising from the substance or mixture

**Hazardous combustion products:** Carbon oxides. Silicon oxides.

**Unusual Fire and Explosion Hazards:** Exposure to combustion products may be a hazard to health..

### 5.3 Advice for firefighters

**Fire Fighting Procedures:** Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

**Special protective equipment for firefighters:** Wear self-contained breathing apparatus for firefighting if necessary.. Use personal protective equipment..

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**6.1 Personal precautions, protective equipment and emergency procedures:** Follow safe handling advice and personal protective equipment recommendations.

**6.2 Environmental precautions:** Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**6.3 Methods and materials for containment and cleaning up:** Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 6 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

### 6.4 Reference to other sections:

See sections: 7, 8, 11, 12 and 13.

## SECTION 7: HANDLING AND STORAGE

**7.1 Precautions for safe handling:** Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

**7.2 Conditions for safe storage, including any incompatibilities:** Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents.

Unsuitable materials for containers: None known.

**7.3 Specific end use(s):** See the technical data sheet on this product for further information.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

| Component                                                             | Regulation                                                                                                                                                                                                                                                                                | Type of listing | Value                                           |
|-----------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-------------------------------------------------|
| Distillates (petroleum), hydro- treated light; Kerosine — unspecified | ACGIH                                                                                                                                                                                                                                                                                     | TWA             | 200 mg/m <sup>3</sup> , total hydrocarbon vapor |
|                                                                       | Further information: CNS impair: Central Nervous System impairment; URT irr: Upper Respiratory Tract irritation; skin irr: Skin irritation; P: Application restricted to conditions in which there are negligible aerosol exposures; Skin: Danger of cutaneous absorption; varies: varies |                 |                                                 |
|                                                                       | IHG                                                                                                                                                                                                                                                                                       | TWA             | 100 ppm                                         |
|                                                                       | IHG                                                                                                                                                                                                                                                                                       | STEL            | 125 ppm                                         |
| octamethylcyclotetrasiloxane                                          | US WEEL                                                                                                                                                                                                                                                                                   | TWA             | 10 ppm                                          |
| 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one                           | IHG                                                                                                                                                                                                                                                                                       | TWA             | 0,06 mg/m <sup>3</sup>                          |
|                                                                       | IHG                                                                                                                                                                                                                                                                                       | STEL            | 0,1 mg/m <sup>3</sup>                           |
| Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane              | ACGIH                                                                                                                                                                                                                                                                                     | TWA             | 0,1 mg/m <sup>3</sup> , Tin                     |
|                                                                       | Further information: A4: Not classifiable as a human carcinogen; Skin: Danger of cutaneous absorption                                                                                                                                                                                     |                 |                                                 |
|                                                                       | ACGIH                                                                                                                                                                                                                                                                                     | STEL            | 0,2 mg/m <sup>3</sup> , Tin                     |
|                                                                       | Further information: A4: Not classifiable as a human carcinogen; Skin: Danger of cutaneous absorption                                                                                                                                                                                     |                 |                                                 |

### Recommended monitoring procedures

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with the Occupational Exposure Limits and the adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

**SAFETY DATA SHEET**

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 7 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

Validated exposure measurement methods should be applied by a competent person and samples should be analysed by an accredited laboratory.

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy); European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents); European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods.

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods.

Health and Safety Executive (HSE), United Kingdom: Methods for the Determination of Hazardous Substances.

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany.

L'Institut National de Recherche et de Sécurité, (INRS), France.

**Derived No Effect Level**

Distillates (petroleum), hydro- treated light; Kerosine — unspecified

**Workers**

| <i>Acute systemic effects</i> |            | <i>Acute local effects</i> |            | <i>Long-term systemic effects</i> |             | <i>Long-term local effects</i> |            |
|-------------------------------|------------|----------------------------|------------|-----------------------------------|-------------|--------------------------------|------------|
| Dermal                        | Inhalation | Dermal                     | Inhalation | Dermal                            | Inhalation  | Dermal                         | Inhalation |
| n.a.                          | n.a.       | n.a.                       | n.a.       | 0,500 mg/kg bw/day                | 0,010 mg/m3 | n.a.                           | n.a.       |

**Consumers**

| <i>Acute systemic effects</i> |            |                     | <i>Acute local effects</i> |            | <i>Long-term systemic effects</i> |            |                       | <i>Long-term local effects</i> |            |
|-------------------------------|------------|---------------------|----------------------------|------------|-----------------------------------|------------|-----------------------|--------------------------------|------------|
| Dermal                        | Inhalation | Oral                | Dermal                     | Inhalation | Dermal                            | Inhalation | Oral                  | Dermal                         | Inhalation |
| n.a.                          | n.a.       | 0,0015 mg/kg bw/day | n.a.                       | n.a.       | n.a.                              | n.a.       | 0,000250 mg/kg bw/day | n.a.                           | n.a.       |

octamethylcyclotetrasiloxane

**Workers**

| <i>Acute systemic effects</i> |            | <i>Acute local effects</i> |            | <i>Long-term systemic effects</i> |            | <i>Long-term local effects</i> |            |
|-------------------------------|------------|----------------------------|------------|-----------------------------------|------------|--------------------------------|------------|
| Dermal                        | Inhalation | Dermal                     | Inhalation | Dermal                            | Inhalation | Dermal                         | Inhalation |
| n.a.                          | n.a.       | n.a.                       | n.a.       | n.a.                              | 73 mg/m3   | n.a.                           | 73 mg/m3   |

**Consumers**

| <i>Acute systemic effects</i> |            |      | <i>Acute local effects</i> |            | <i>Long-term systemic effects</i> |            |                  | <i>Long-term local effects</i> |            |
|-------------------------------|------------|------|----------------------------|------------|-----------------------------------|------------|------------------|--------------------------------|------------|
| Dermal                        | Inhalation | Oral | Dermal                     | Inhalation | Dermal                            | Inhalation | Oral             | Dermal                         | Inhalation |
| n.a.                          | n.a.       | n.a. | n.a.                       | n.a.       | n.a.                              | 13 mg/m3   | 3,7 mg/kg bw/day | n.a.                           | 13 mg/m3   |

**SAFETY DATA SHEET**

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 8 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

**Predicted No Effect Concentration**

Distillates (petroleum), hydro- treated light; Kerosine — unspecified

| Compartment              | PNEC                        |
|--------------------------|-----------------------------|
| Fresh water              | 0,00914 mg/l                |
| Intermittent use/release | 0,320 mg/l                  |
| Marine water             | 0,000914 mg/l               |
| Sewage treatment plant   | 100 mg/l                    |
| Fresh water sediment     | 140 mg/kg dry weight (d.w.) |
| Marine sediment          | 14 mg/kg dry weight (d.w.)  |
| Soil                     | 28 mg/kg dry weight (d.w.)  |
| Oral                     | 0,138 mg/kg food            |

octamethylcyclotetrasiloxane

| Compartment            | PNEC          |
|------------------------|---------------|
| Fresh water            | 0,0015 mg/l   |
| Marine water           | 0,00015 mg/l  |
| Fresh water sediment   | 3 mg/kg       |
| Marine sediment        | 0,3 mg/kg     |
| Soil                   | 0,54 mg/kg    |
| Sewage treatment plant | 10 mg/l       |
| Oral                   | 41 mg/kg food |

4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

| Compartment                | PNEC            |
|----------------------------|-----------------|
| Fresh water                | 0,034 µg/l      |
| Fresh water sediment       | 0,41 mg/kg      |
| Marine sediment            | 0,0034 mg/kg    |
| Sewage treatment plant     | 0,064 mg/l      |
| Soil                       | 0,062 mg/kg     |
| Oral (Secondary Poisoning) | 4,49 mg/kg food |
| Marine water               | 0,0068 µg/l     |

**8.2 Exposure controls**

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

**Individual protection measures**

**Eye/face protection:** Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent. If exposure causes eye discomfort, use a full-face respirator (meeting standard EN 136) with organic vapor cartridge (meeting standard EN 14387).

**Skin protection**

**Hand protection:** Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate

**SAFETY DATA SHEET**  
**According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH**

EDD SILICONE ACETICO TRASPARENTE AU11  
cod.85551001  
Versione: 7.1/ EN

Pag. 9 di 27

Print Date: 06/04/2023  
Revision Date: 06/04/2023

("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

Use the following CE approved air-purifying respirator: Organic vapor cartridge, type A (boiling point >65 °C, meeting standard EN 14387).

#### **Environmental exposure controls**

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

---

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

### **9.1 Information on basic physical and chemical properties**

#### **Appearance**

|                              |                                                             |
|------------------------------|-------------------------------------------------------------|
| Physical state               | thixotropic paste                                           |
| Color                        | transparent, colourless                                     |
| Odor                         | acetic acid                                                 |
| Odor Threshold               | No data available                                           |
| pH                           | Not applicable, substance/mixture is non-soluble (in water) |
| Melting point/freezing point |                                                             |
| Melting point/range          | No data available                                           |
| Freezing point               | not determined                                              |

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 10 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

### Boiling point or initial boiling point and boiling range

Boiling point (760 mmHg) Not applicable

Flash point **closed cup** >100 °C

Flammability (solid, gas) Not classified as a flammability hazard

Flammability (liquids) Not applicable, solid

Lower explosion limit No data available

Upper explosion limit No data available

Vapor Pressure Not applicable

Relative Vapor Density (air = 1) No data available

Relative Density (water = 1) 0,96

### Solubility(ies)

Water solubility insoluble

Partition coefficient: n-octanol/water not determined (Mixture)

Auto-ignition temperature No data available

Decomposition temperature No data available

Kinematic Viscosity >20,5 mm<sup>2</sup>/s (at +40°C)

### Particle characteristics

Particle size not determined (Not a solid)

## 9.2 Other information

Molecular weight No data available

Dynamic Viscosity Not applicable

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Self-heating substances The substance or mixture is not classified as self heating.

Evaporation Rate (Butyl Acetate = 1) Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

## SECTION 10: STABILITY AND REACTIVITY

**10.1 Reactivity:** Not classified as a reactivity hazard.

**10.2 Chemical stability:** Stable under normal conditions.

**10.3 Possibility of hazardous reactions:** Can react with strong oxidizing agents.

**10.4 Conditions to avoid:** None known.

**10.5 Incompatible materials:** Avoid contact with oxidizing materials.

### 10.6 Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde.

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 11 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

Eye contact, Skin contact, Ingestion.

**Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)**

#### Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 5 000 mg/kg Estimated.

#### Information for components:

##### Distillates (petroleum), hydro- treated light; Kerosine — unspecified

Single dose oral LD50 has not been determined.

For similar material(s): LD50, Rat, > 5 000 mg/kg

##### Distillates (petroleum), hydrotreated middle; Gasoil — unspecified

LD50, Rat, > 5 000 mg/kg

##### octamethylcyclotetrasiloxane

LD50, Rat, male, > 4 800 mg/kg No deaths occurred at this concentration.

##### 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

Acute toxicity estimate, 567 mg/kg Acute toxicity estimate according to Regulation (EC) No. 1272/2008

##### Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

LD50, Rat, male and female, 892 mg/kg OECD 401 or equivalent

#### Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, Rabbit, > 2 000 mg/kg Estimated.

#### Information for components:

##### Distillates (petroleum), hydro- treated light; Kerosine — unspecified

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 12 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

The dermal LD50 has not been determined.

For similar material(s): LD50, Rabbit, > 5 000 mg/kg Estimated.

**Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

LD50, Rabbit, > 3 160 mg/kg No deaths occurred at this concentration.

**octamethylcyclotetrasiloxane**

LD50, Rat, male and female, > 2 400 mg/kg No deaths occurred at this concentration.

**4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

No deaths occurred at this concentration. LD50, Rabbit, > 2 000 mg/kg OECD Test Guideline 402

**Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

LD50, Rat, > 2 000 mg/kg

**Acute inhalation toxicity**

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

**Information for components:**

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

The LC50 has not been determined.

For similar material(s): LC50, Rat, 8 Hour, vapour, > 5 mg/l

**Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

LC50, Rat, 4 Hour, dust/mist, > 5,2 mg/l

**octamethylcyclotetrasiloxane**

LC50, Rat, male and female, 4 Hour, dust/mist, 36 mg/l OECD Test Guideline 403

**4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

Acute toxicity estimate, dust/mist, 0,16 mg/l Acute toxicity estimate according to Regulation (EC) No. 1272/2008

**Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

As product: The LC50 has not been determined.

**Skin corrosion/irritation**

Based on information for component(s):

Brief contact may cause slight skin irritation with local redness.

May cause drying and flaking of the skin.

**Information for components:**

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

For similar material(s):

Brief contact may cause slight skin irritation with local redness.

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 13 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

May cause drying and flaking of the skin.

### **Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

Brief contact may cause slight skin irritation with local redness.

### **octamethylcyclotetrasiloxane**

Brief contact is essentially nonirritating to skin.

### **4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

Brief contact may cause severe skin burns. Symptoms may include pain, severe local redness and tissue damage.

### **Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

Brief contact may cause skin irritation with local redness.

### **Serious eye damage/eye irritation**

Based on information for component(s):

May cause slight eye irritation.

Vapor may cause eye irritation experienced as mild discomfort and redness.

May cause mild eye discomfort.

### **Information for components:**

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

May cause slight eye irritation.

Corneal injury is unlikely.

Vapor may cause eye irritation experienced as mild discomfort and redness.

#### **Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

May cause slight eye irritation.

#### **octamethylcyclotetrasiloxane**

Essentially nonirritating to eyes.

#### **4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

#### **Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

May cause slight eye irritation.

May cause slight temporary corneal injury.

### **Sensitization**

For skin sensitization:

Based on product testing:

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

### **Information for components:**

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 14 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

For similar material(s):

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

### **Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

For similar material(s):

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

### **octamethylcyclotetrasiloxane**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

### **4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

### **Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

## **Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

## **Information for components:**

### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

### **Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

Available data are inadequate to determine single exposure specific target organ toxicity.

### **octamethylcyclotetrasiloxane**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

### **4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

May cause respiratory irritation.

Route of Exposure: Inhalation

Target Organs: Respiratory Tract

### **Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

Available data are inadequate to determine single exposure specific target organ toxicity.

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 15 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

### Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

### Information for components:

#### Distillates (petroleum), hydro- treated light; Kerosine — unspecified

May be fatal if swallowed and enters airways.

#### Distillates (petroleum), hydrotreated middle; Gasoil — unspecified

May be fatal if swallowed and enters airways.

#### octamethylcyclotetrasiloxane

May be harmful if swallowed and enters airways.

#### 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

Aspiration into the respiratory system may occur during ingestion or vomiting. Due to corrosivity, tissue damage or lung injury may occur.

#### Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Based on physical properties, not likely to be an aspiration hazard.

**Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)**

### Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in animals:  
Kidney.

### Information for components:

#### Distillates (petroleum), hydro- treated light; Kerosine — unspecified

In animals, effects have been reported on the following organs:  
Kidney.

#### Distillates (petroleum), hydrotreated middle; Gasoil — unspecified

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

#### octamethylcyclotetrasiloxane

In animals, effects have been reported on the following organs:  
Kidney.  
Liver.  
Respiratory tract.  
Female reproductive organs.

#### 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

In animals, effects have been reported on the following organs:  
Stomach.

#### Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

In animals, effects have been reported on the following organs:  
Blood  
Kidney

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 16 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

Liver  
Immune system.

### Carcinogenicity

Contains component(s) which did not cause cancer in laboratory animals.

### Information for components:

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

For similar material(s): Did not cause cancer in laboratory animals.

#### **Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

For similar material(s): Did not cause cancer in laboratory animals.

#### **octamethylcyclotetrasiloxane**

Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

#### **4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

No relevant data found.

#### **Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

No relevant data found.

### Teratogenicity

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

### Information for components:

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

#### **Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

#### **octamethylcyclotetrasiloxane**

Did not cause birth defects or any other fetal effects in laboratory animals.

#### **4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

Did not cause birth defects or any other fetal effects in laboratory animals.

#### **Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

No relevant data found.

### Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 17 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

### Information for components:

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

For similar material(s): In animal studies, did not interfere with reproduction.

**Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

For similar material(s): In animal studies, did not interfere with reproduction.

**octamethylcyclotetrasiloxane**

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. In animal studies, has been shown to interfere with fertility.

**4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

In animal studies, did not interfere with reproduction.

**Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

No relevant data found.

### Mutagenicity

In vitro genetic toxicity studies were negative for component(s) tested. Genetic toxicity studies in animals were negative for component(s) tested.

### Information for components:

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

For similar material(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**octamethylcyclotetrasiloxane**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

### 11.2 Information on other hazards

#### Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Information for components:

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 18 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

### **Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

### **octamethylcyclotetrasiloxane**

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

### **4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

### **Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

---

## **SECTION 12: ECOLOGICAL INFORMATION**

---

### **12.1 Toxicity**

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

##### **Acute toxicity to fish**

Not expected to be acutely toxic to aquatic organisms.

#### **Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

##### **Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LL50, *Scophthalmus maximus* (turbot), 96 Hour, > 1 028 mg/l, Test substance: Water Accommodated Fraction

##### **Acute toxicity to aquatic invertebrates**

LL50, *Acartia tonsa*, 48 Hour, > 3 193 mg/l, Test substance: Water Accommodated Fraction

##### **Acute toxicity to algae/aquatic plants**

EL50, *Skeletonema costatum* (marine diatom), 72 Hour, > 10 000 mg/l, Test substance: Water Accommodated Fraction

##### **Toxicity to bacteria**

EC50, 3 Hour, > 100 mg/l, OECD Test Guideline 209

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 19 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

### **Chronic toxicity to aquatic invertebrates**

NOELR, Ceriodaphnia dubia (water flea), 8 d, > 100 mg/l, Test substance: Water  
Accommodated Fraction

### **octamethylcyclotetrasiloxane**

#### **Acute toxicity to fish**

Based on testing of comparable products: The estimated maximum aqueous concentration of Octamethyl Cyclotetrasiloxane (D4) from migration to water from the product as supplied is below the D4 established no-effect threshold (< 0.0079 mg/L) for aquatic organisms.

#### **Chronic toxicity to aquatic invertebrates**

Based on testing for product(s) in this family of materials:  
Not classified due to data which are conclusive although insufficient for classification.

### **4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

#### **Acute toxicity to fish**

Material is very toxic to aquatic organisms (LC50/EC50/IC50 below 1 mg/L in the most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), flow-through, 96 Hour, 0,0027 mg/l, OECD Test Guideline 203 or Equivalent

LC50, Bluegill sunfish (Lepomis macrochirus), flow-through, 96 Hour, 0,014 mg/l, OECD Test Guideline 203 or Equivalent

#### **Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, 0,0057 mg/l

#### **Acute toxicity to algae/aquatic plants**

EbC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, 0,048 mg/l, OECD Test Guideline 201

ErC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, 0,077 mg/l, OECD Test Guideline 201

#### **Toxicity to bacteria**

EC50, activated sludge, Respiration rates., 5,70 mg/l

#### **Chronic toxicity to fish**

NOEC, Oncorhynchus mykiss (rainbow trout), flow-through, 97 d, growth, 0,00056 mg/l

#### **Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 21 d, 0,00063 mg/l

### **Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy]((dimethyl)stannane**

#### **Acute toxicity to fish**

Material is harmful to aquatic organisms (LC50/EC50/IC50 between 10 and 100 mg/L in the most sensitive species).

For similar material(s):

LC50, Zebra fish (Danio/Brachydanio rerio), semi-static test, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

#### **Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna, static test, 48 Hour, 39 mg/l, OECD Test Guideline 202 or Equivalent

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 20 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

### Acute toxicity to algae/aquatic plants

ErC50, Algae (*Scenedesmus subspicatus*), Growth rate, 72 Hour, Growth rate, 7,6 mg/l,  
OECD Test Guideline 201 or Equivalent

For similar material(s):

NOEC, Algae (*Scenedesmus subspicatus*), Growth rate, 72 Hour, Growth rate, 1,1 mg/l,  
OECD Test Guideline 201 or Equivalent

### Toxicity to bacteria

For similar material(s):

EC50, Bacteria, 3 Hour, Respiration rates., 14 mg/l

## 12.2 Persistence and degradability

### Distillates (petroleum), hydro- treated light; Kerosine — unspecified

**Biodegradability:** Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail

**Biodegradation:** 4 - 12 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301D or Equivalent

### Distillates (petroleum), hydrotreated middle; Gasoil — unspecified

**Biodegradability:** Material is expected to be readily biodegradable.

10-day Window: Not applicable

**Biodegradation:** 74 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 306

### octamethylcyclotetrasiloxane

**Biodegradability:** Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable

**Biodegradation:** 3,7 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 310

### Stability in Water (1/2-life)

Hydrolysis, DT50, 3,9 d, pH 7, Half-life Temperature 25 °C, OECD Test Guideline 111

### 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

**Biodegradability:** Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.  
Considered to be rapidly degradable.

### Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

**Biodegradability:** For similar material(s): Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

For similar material(s): 10-day Window: Fail

**Biodegradation:** 3 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301F or Equivalent

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 21 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

### 12.3 Bioaccumulative potential

#### Distillates (petroleum), hydro- treated light; Kerosine — unspecified

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

**Partition coefficient: n-octanol/water(log Pow):** 3,3 - 6 estimated

**Bioconcentration factor (BCF):** 310 Fish Estimated.

#### Distillates (petroleum), hydrotreated middle; Gasoil — unspecified

**Bioaccumulation:** No relevant data found.

#### octamethylcyclotetrasiloxane

**Bioaccumulation:** Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

**Partition coefficient: n-octanol/water(log Pow):** 6,49 Measured

**Bioconcentration factor (BCF):** 12 400 Pimephales promelas (fathead minnow) Measured

#### 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 2,8 Measured

**Bioconcentration factor (BCF):** < 13 Fish

#### Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

**Bioaccumulation:** No relevant data found.

### 12.4 Mobility in soil

#### Distillates (petroleum), hydro- treated light; Kerosine — unspecified

**Partition coefficient (Koc):** > 5000 Estimated.

#### Distillates (petroleum), hydrotreated middle; Gasoil — unspecified

No relevant data found.

#### octamethylcyclotetrasiloxane

**Partition coefficient (Koc):** 16596 OECD Test Guideline 106

#### 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

**Partition coefficient (Koc):** 5662 - 7865 Measured

#### Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

### 12.5 Results of PBT and vPvB assessment

#### Distillates (petroleum), hydro- treated light; Kerosine — unspecified

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

#### Distillates (petroleum), hydrotreated middle; Gasoil — unspecified

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

#### octamethylcyclotetrasiloxane

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 22 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

Octamethylcyclotetrasiloxane (D4) meets the current criteria for PBT and vPvB under REACH Annex XIII or other regionally specific criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms. Decamethylcyclopentasiloxane (D5) meets the current REACH Annex XIII criteria for vPvB. However, D5 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D5 is not biomagnifying in aquatic and terrestrial food webs. D5 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D5 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

This substance is considered to be persistent, bioaccumulating and toxic (PBT).

### **4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

### **Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

## **12.6 Endocrine disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified**

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

### **Distillates (petroleum), hydrotreated middle; Gasoil — unspecified**

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

### **octamethylcyclotetrasiloxane**

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

### **4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one**

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

### **Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane**

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 23 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

### 12.7 Other adverse effects

#### Distillates (petroleum), hydro- treated light; Kerosine — unspecified

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

#### Distillates (petroleum), hydrotreated middle; Gasoil — unspecified

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

#### octamethylcyclotetrasiloxane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

#### 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

#### Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

---

## SECTION 13: DISPOSAL CONSIDERATIONS

---

### 13.1 Waste treatment methods

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

---

## SECTION 14: TRANSPORT INFORMATION

---

### Classification for ROAD and Rail transport (ADR/RID):

- |                                   |                                                                   |
|-----------------------------------|-------------------------------------------------------------------|
| 14.1 UN number or ID number       | Not applicable                                                    |
| 14.2 UN proper shipping name      | Not regulated for transport                                       |
| 14.3 Transport hazard class(es)   | Not applicable                                                    |
| 14.4 Packing group                | Not applicable                                                    |
| 14.5 Environmental hazards        | Not considered environmentally hazardous based on available data. |
| 14.6 Special precautions for user | No data available.                                                |

### Classification for SEA transport (IMO-IMDG):

- |                              |                             |
|------------------------------|-----------------------------|
| 14.1 UN number or ID number  | Not applicable              |
| 14.2 UN proper shipping name | Not regulated for transport |

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 24 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

- |                                                                     |                                                             |
|---------------------------------------------------------------------|-------------------------------------------------------------|
| <b>14.3 Transport hazard class(es)</b>                              | Not applicable                                              |
| <b>14.4 Packing group</b>                                           | Not applicable                                              |
| <b>14.5 Environmental hazards</b>                                   | Not considered as marine pollutant based on available data. |
| <b>14.6 Special precautions for user</b>                            | No data available.                                          |
| <b>14.7 Maritime transport in bulk according to IMO instruments</b> | Consult IMO regulations before transporting ocean bulk      |

### Classification for AIR transport (IATA/ICAO):

- |                                          |                             |
|------------------------------------------|-----------------------------|
| <b>14.1 UN number or ID number</b>       | Not applicable              |
| <b>14.2 UN proper shipping name</b>      | Not regulated for transport |
| <b>14.3 Transport hazard class(es)</b>   | Not applicable              |
| <b>14.4 Packing group</b>                | Not applicable              |
| <b>14.5 Environmental hazards</b>        | Not applicable              |
| <b>14.6 Special precautions for user</b> | No data available.          |

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

## SECTION 15: REGULATORY INFORMATION

---

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### REACH Regulation (EC) No 1907/2006

This product contains only components that have been either registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No.

1907/2006 (REACH). The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

#### REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:  
octamethylcyclotetrasiloxane (Number on list 70)  
Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane (Number on list 20)

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 25 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

### Authorisation status under REACH:

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

CAS-No.: 556-67-2

Name: octamethylcyclotetrasiloxane

Authorisation status: listed in the Candidate List of Substances of Very High Concern for Authorisation

Authorisation number: Not available

Sunset date: Not available

Exempted (Categories of) Uses: Not available

### Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Number in Regulation: 34

2 500 t

25 000 t

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture.

---

## SECTION 16: OTHER INFORMATION

---

### Full text of H-Statements referred to under sections 2 and 3.

|       |                                                       |
|-------|-------------------------------------------------------|
| H226  | Flammable liquid and vapour.                          |
| H302  | Harmful if swallowed.                                 |
| H304  | May be fatal if swallowed and enters airways.         |
| H314  | Causes severe skin burns and eye damage.              |
| H315  | Causes skin irritation.                               |
| H317  | May cause an allergic skin reaction.                  |
| H318  | Causes serious eye damage.                            |
| H330  | Fatal if inhaled.                                     |
| H335  | May cause respiratory irritation.                     |
| H361f | Suspected of damaging fertility.                      |
| H400  | Very toxic to aquatic life.                           |
| H410  | Very toxic to aquatic life with long lasting effects. |
| H412  | Harmful to aquatic life with long lasting effects.    |

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Aquatic Chronic - 3 - H412 - Calculation method

### Revision

Sections from 1 to 16

**SAFETY DATA SHEET****According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH**

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 26 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

**Legend**

|                 |                                                     |
|-----------------|-----------------------------------------------------|
| ACGIH           | USA. ACGIH Threshold Limit Values (TLV)             |
| IHG             | Industrial Hygiene Guideline                        |
| STEL            | Short term exposure limit                           |
| TWA             | Time weighted average                               |
| US WEEL         | USA. Workplace Environmental Exposure Levels (WEEL) |
| Acute Tox.      | Acute toxicity                                      |
| Aquatic Acute   | Short-term (acute) aquatic hazard                   |
| Aquatic Chronic | Long-term (chronic) aquatic hazard                  |
| Asp. Tox.       | Aspiration hazard                                   |
| Eye Dam.        | Serious eye damage                                  |
| Flam. Liq.      | Flammable liquids                                   |
| Repr.           | Reproductive toxicity                               |
| Skin Corr.      | Skin corrosion                                      |
| Skin Irrit.     | Skin irritation                                     |
| Skin Sens.      | Skin sensitisation                                  |
| STOT SE         | Specific target organ toxicity - single exposure    |

**Full text of other abbreviations**

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Information Source and References**

## SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

EDD SILICONE ACETICO TRASPARENTE AU11

cod.85551001

Versione: 7.1/ EN

Pag. 27 di 27

Print Date: 06/04/2023

Revision Date: 06/04/2023

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

Saratoga Int. Sforza S.p.A. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

IT

### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)