Via Edison, 76 - 20090 Trezzano sul Naviglio (MILANO) - ITALY TEL. +39.02.445731 - www.saratoga.it

Saratoga Bitumì Guaina Liquida

Saratoga Bitumì Liquid Sheath is the quick one-component synthetic rubber-based quick finish, ideal for waterproofing, protecting and repairing.

APPLICATION FIELDS

It's suitable for both indoor and outdoor applications, it is particularly suitable for waterproofing: showers and bathrooms, joints between different sheaths, flooring and walls, under-tile in wet rooms, cracks in roof transitions and penetrations, window frames and skylight joints. It is also ideal for repairs of: edges of sheaths that detach, gutters, corrugated sheets and for insulation of air and water joints. Suitable for: roofing, fiber cement slabs, low footfall terraces, roof tiles, tiles, pipes, chimney pots, skylights, flashings, drains, pots. Ideal for all surfaces, it's particularly suitable on: screed, concrete, bitumen, metal sheets, alluminum, steel and woods. Totally impermeable to air and water, it is self-levelling and elastic, protects against corrosion and erosion, is plasticiser-free, VOC-free, solvent-free and odourless.

Also suitable for flat surfaces, without slope.

Ready to use, it is easy to apply with a brush, does not shrink and it's overpaintable. It covers and protects surfaces without affecting them. It can be applied starting from 0°C.

APPLICATION

- Make sure that the surfaces to be treated are clean, dry and degreased. Sand if necessary.
- For application on very porous surfaces, prime with Saratoga Mix1000 in a ratio of 1:1 (1 part of water to 1 part of Mix1000).
- Mix with a spatula before use, until uniformly colored.
- Apply evenly with a brush (you can also apply by roller if necessary) at least 2 coats of about 0.5 mm each, waiting about 1 hour (skin time) between the two applications.
- One completely dry (about 12 hours), make sure you have applied a total thickness of at least 1 mm.
- Consider at least doubled timelines in case of application in cold weather.

Cleaning: immediate with water, when cured remove with a razor blade.

Yield: a jar is indicated for about 1 m².

STORAGE AND SHELF LIFE

In unopened original packaging, between +20°C and +25°C.

CAUTIONS

Keep out of reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Color	Pack size	Product code	Box quantity	EAN Code
Black	750 ml	54.185.001	8	8 005860 541856



25/08/2023, 1st Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.