

Saratoga Fernovus Lamiere Zincate

Saratoga Fernovus Lamiere Zincate is the protective and decorative enamel for direct treatment on metals of various kinds such as galvanized sheet metal and steel and on non-ferrous metals such as aluminum, copper and brass. It can be applied in a single coat without the need for a primer.

Easy to use, it has been formulated to provide excellent coverage in one coat. It doesn't drip.

APPLICATION FIELDS

Ideal both outdoors and indoors, it is also used on elements exposed to the elements such as garage doors, shutters, windows, railings, fences, gates, pipes, front doors, gutters, outdoor furniture, boxes and decorative objects.

APPLICATION

Mix well with a spatula until you get a homogeneous consistency.

New and smooth surface:

- Sand;
- Clean, degrease and dry;
- Apply Fernovus Lamiere Zincate

Old and treated surfaces:

- Sand;
- Remove non-adherent oxide, old paints and any rust;
- Clean, degrease and dry;
- Apply Fernovus Lamiere Zincate.

Already painted surfaces:

- Test on hidden part of the article in advance.
- After 2-3 hours, if the product is well anchored to the surface, continue with all work.
- If the original color is very different from the one applied, you may need a second coat to perfectly cover and even the color.
- Cover corners and edges well with paint.

Cleaning tools: remove excess paint from the working tools, then clean with turpentine.

Store in a dry and well ventilated place; keep away from frost, high temperatures and direct sunlight.

SPECIFIC DATA:

Appearance	Compact gel
Specific weight (g/ml)	abt. 1
Dry to the touch	After 4 h
Minimum time between 1st and 2nd hand	8 h
Application with brush	Ready to use, do not dilute, do not add dyes 5-10% with turpentine and mix before applying 5-10% with turpentine and mix before applying
with roller	
spraying	
Application temperature	From +5°C to +35°C
Temperature resistance	-20°C to +70°C
Yield for hand	abt. 14 m ² /l
Dry residue (% p/p)	abt. 50
Film thickness (for hand)	30 μ (dry)

STORAGE AND SHELF LIFE

In unopened original packaging, between +20°C and +25°C.

CAUTIONS

Keep out of reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product description	Pack size	Product code	Box quantity	EAN Code
Fernovus Lamiere Zincate Metal Grey	750 ml	88641001	6	8005860886414
Fernovus Lamiere Zincate Brown	750 ml	88641002	6	8005860916432
Fernovus Lamiere Zincate White	750 ml	88641003	6	8005860916449
Fernovus Lamiere Zincate Green	750 ml	88641004	6	8005860916456



28/02/2024, 1st Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings . All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.