

Saratoga Anti-scivolo Vernice Spray

Saratoga Anti-slippery Spray Paint is the fast-drying transparent acrylic paint with non-slip microspheres that gives high grip, especially on slippery surfaces. UV resistant.

It is transparent with a micro-rough effect and does not turn yellow.

APPLICATION FIELDS

For indoor and outdoor use, it is resistant to bad weather, light, aggressive environments (with good resistance to salt and chlorine). Suitable for concrete, screeds, ceramic and clinker tiles, ABS, wood (as long as it has not previously been treated with oils), glass, metals (iron, brass, aluminium).

It is ideal on stairs, walkways, shower trays, bathrooms, damp or slippery environments, service areas, floors, handrails and walkable surfaces. Also suitable for round or curved surfaces.

APPLICATION

- Apply to clean, dry, degreased, rust-free and crumbly surfaces.
- Mask parts not to be treated.
- Shake the can vigorously until you hear the sound of the balls inside, continuing the action for another minute.
- Apply the contents of the can to the surfaces to be treated, you can use the can at an angle of up to 90°; in case of dispensing interruptions, shake the can again. Do not apply upside down.
- Apply from approx. 20-25 cm apart in thin layers, with an interval of 3-5 minutes between each hand.
- Do not step on before the paint is deep dry.
- Do not apply to synthetic paints; for all other paints, carry out a compatibility test beforehand.

Ideal application conditions between +10°C and +25°C, in a cool place, with max humidity 60% and no wind.

If used on plastic or aluminium, use a primer such as Happy Color Primer beforehand.

The Anti-Slip Paint is an excellent adjuvant in terms of increasing surface roughness; in any case, always pay attention to all surfaces, even when treated.

Yield: one can covers about 1.5-2 m².

Cleansing: immediate with acetone; mechanical (ex. by sanding) once dry.

Specific Data	
Appearance	Transparent with microspheres
Odour	Solvent Characteristic
Application temperature	+10°/+30°C
Dry to the touch after	20 minutes
Deep dry after	24 hours
Yield (for one cane)	about 1,5-2 m ²

STORAGE AND SHELF LIFE

In unopened original packaging, between +20°C and +25°C.

CAUTIONS

Keep out of reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product description	Pack size	Product code	Box quantity	EAN Code
Anti-slippery Spray Paint	400 ml	54.190.001	6	8 005860 541900
Anti-slippery Spray Paint with display	400 ml	54.190.002	6	8 005860 541900



07/02/2024, 1st Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings . All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.