

Saratoga Vernice per Box

Saratoga Varnish for Garages is the high-performance water-based one-component coating. It is walkable, trailerable and vehicles accessible; ideal for both existing and new floors, indoor and outdoor, resistant to bad weather, frost, high temperatures. It has a consolidating effect on the floor. With high adhesion, it is resistant to the passage of cars, abrasion and wear, it is anti-dust.

APPLICATION FIELDS

Saratoga Varnish for Garages is ideal for protecting and restoring cement and concrete floors, interlocking bricks, briks, single-fired ceramic, cotto and gres tiles, etc. Suitable for garages, mechanics workshops, battery rooms, small warehouses, production areas, boiler rooms, attics, cellars, etc.

Resistant to hot tires, engine oil, hydraulic oil, antifreeze stains.

APPLICATION

- Surfaces must be clean, dry, degreased, free of crumbly parts.
- In case of obvious oil stains, first treat with a specific stain remover, then apply Saratoga Varnish for Garages.
- To ensure maximum adhesion, on non-absorbent surfaces, sand with suitable coarse sandpaper or abrasive discs.
- On moist substrates or in presence of water counter-thrusts or on oil and grease stained floors, clean carefully using suitable detergent solutions and let dry.
- Ready-to-use: blend the product before application.
- Apply the product with a short-haired roller or brush or spray (diluting the product with 5% water).
- Possible second coat (diluting the product with 5% water) after about 4-6 hours, in case exceeding 72 hours between one coat and other, then before sand with fine sandpaper to ensure good adhesion.
- For more protection, it is possible to give a third coat following the above instructions.

On delicate or non-absorbent surfaces, always test before on a small part of the floor.

CLEANING TOOLS: right after application with water.

For daily cleaning use a floor cleaner (such as Saratoga Nettatutto) and rise with water or a garden hose.

Specific data	
Appearance	Thick liquid
Color	Transparent*; Grey
Secon hand after	around 4-6 hours
Walkable after	24 hours
Trailerable after	72 hours
Vehicle accessible after	72 hours
Application Temperature	+10° / +35°C
Temperature resistance	-30°/ +100°C
Yiel	around 10 m2/l

*The transparent colored product is milky white in mass, it becomes transparent once applied and dry

STORAGE AND SHELF LIFE

In unopened original packaging, between +20°C and +25°C.

CAUTIONS

Keep out of reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Color	Box quantity	EAN Code
Varnish for Garages	750 ml	54 095 001	Transparent	6	8 005860 540958
Varnish for Garages	750 ml	54 095 002	Grey	6	8 005860 915138



29/05/2023, 2nd Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings . All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.