

## Saratoga HD350 Competition Motor Sealant

Saratoga HD 350 Competition Motor Sealant is an acetic one-component silicone sealant in red dough, with exceptional heat resistance, that cures quickly thanks to the atmospheric humidity, creating extremely elastic and resistant seals.

### APPLICATION FIELDS

Saratoga HD 350 Competition Motor Sealant has very high heat resistance features and therefore is the ideal seal for motor industry.

Suitable for uses which temperatures are between -60 and +260°C, with peaks up to 350°C; has very high resistance to UV rays, atmospheric agents, gas, petrol, naphtha, oils and antifreeze. Has excellent adhesion to glass, ceramic, steel, aluminium, some plastic materials, wood and varnished supports. It is used for sealing gearboxes, oil sump, tappet cover, oil pump and it is specific for all the high practise temperature engine parts. Suited for sealings in heating and air-conditioning systems, it is used also for contact with pipes trasporting hot fluids. In a dismantling phase it can be easily removed and reassembled.

Creates extremely elastic and resistant seals.

### APPLICATION

- All surfaces must be dry, clean, dust free, rust free, degreased and with no detaching materials.
- It is recommended to use a masking tape on both sides of the joint for a better result (remove right after application).
- Parts assembling can be done after 5 minutes from the application and, in any case, not over 20 minutes.
- Remove possible imperfections with a sponge soaked with alcohol or with a blade.
- Polymerizes completely after about 24 hours and, in any case, according to the thickness of the product applied.

### Specific data

Kind of sealant	Acetic silicone sealant
Specific weight	1,04
Consistency	Thixotropic
Extrusion rate	50-70 g/min
Working time	5 minutes
Cure time	3 mm / 24 hours*
Working movement	20%

At 23°C and 50% Relative Humidity

### STORAGE AND SHELF LIFE

Between 20 and 25°C its shelf life is 24 months since manufacturing date.

### CAUTIONS

Keep out of the reach of children.

For uses that need a flame resistant sealant, it is recommended to use Saratoga Mastice Sigillante Refrattario.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site [www.saratoga.it](http://www.saratoga.it)

Product Description	Pack size	Product code	Box quantity	EAN code
Little tube in case	60 g	85 165 002	8	8 005860 851658



03/17/2015, 1<sup>st</sup> Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings . All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.