

Saratoga Happy Color Insulating Primer for Polystyrene

Saratoga Happy Color Insulating Primer for Polystyrene is a special resins based insulating primer, matte grey coloured.

APPLICATION FIELDS

Saratoga Happy Color Insulating Primer for Polystyrene creates a protective coat for polystyrene surfaces that have to be varnished with the most common solvent spray varnishes. Ideal for all polystyrene surfaces, such as stands, panels, false ceilings, do-it-yourself objects, etc..

APPLICATION

- Use can at about +20/25°C. Shake can energetically upside down for a minute (hearing the sound of the marbles inside the can).
- Spray at 20 cm distance, keeping the can vertically, and shaking it occasionally.
- Apply slight and crossed coats: second coat at any time.
- An even covering, without breaks, is necessary for an excellent protective and insulating effect.
- It is recommended to apply at least 6 coats (3 crossed coats).
- For a better protection on irregular surfaces, apply several coats.
- Apply the varnish with slight and crossed coats: with an abundant coat, an aggression to the polystyrene can happen.

Clean varnish with Acetone and/or Nitro Diluent.

With self-cleaning valve.

Specific data	
Appearance and finishing	Matte
Tack free	10-15 minutes
Fully dry	24-36 hours
Over paintable	2-3 hours (with finishing sprays such as Happy Color)
Colour	Light Grey
Yield	0,5-0,7 mq

STORAGE AND SHELF LIFE

In unopened original packaging, between +20 and +25°.

CAUTIONS

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Box quantity	EAN Code
Can	400 ml	88 160 001	6	8 005860 881600
Can	400 ml	88 160 002	12 in display	8 005860 881600

