Via Edison, 76 - 20090 Trezzano sul Naviglio (MILANO) - ITALY TEL. +39.02.445731 - www.saratoga.it

Saratoga Stucco Rapido Riparatutto- Unistop Rapido for Metal

Saratoga Stucco Rapido Riparatutto is a bi-component epoxy putty which is used for repairing that cures quickly especially on metal. Can be applied in any thickness on metal supports, but also on glass fibre, concrete, wood, marble and ceramic; can be used even underwater (in this case, press vigorously the product to facilitate the adhesion to the support).

APPLICATION FIELDS

Saratoga Stucco Rapido Riparatutto is used to repair holes and pipes' fissures, heaters, radiators, boilers (before using, drain the system), to repair underwater cracks and rifts; it is useful to join different diameters tubes, renew threads, reconstruct missing parts made of wood, marble, ceramic and metal and fill screw holes

For internals and externals, can replace the insulation tape.

APPLICATION AND INSTRUCTIONS

- · Wear appropriate PVC or PE gloves.
- Cut a slide of product and blend the two components until obtaining a uniform paste.
- · All surfaces must be clean, oil free and degreased.
- · Sand the part to repair.
- Apply the product on the part to repair and on the nearby 2 cm.
- Press to facilitate the penetration into the holes and fissures (especially in case of underwater use).
- Keep in place until the adhesion has effect, then shape and cut it with a spatula or a knife.
- If used on a system with a high inner pressure, press until completely cured.

Store in a cool and dry place, out of sunlight.

Clean the fresh product with acetone and degreaser; when cured, clean with a blade.

| Specific data | | | | | |
|-------------------------|--------------------|------------|--|--|--|
| Application temperature | °C | -30 / +140 | | | |
| Shore D Hardness | | 84 | | | |
| Pressure resistance | Kg/cm ² | 600 | | | |
| Tension resistance | Kg/cm ² | 45 | | | |
| Compound colour | | gray | | | |
| Non-volatile content | | ab. 100% | | | |

At 23°C and 50% Relative Humidity

STORAGE AND SHELF LIFE

In unopened original packaging, between +20 and +25°C its shelf life is 24 months since manufacturing date.

CAUTIONS

Keep out of the reach of children.

Store in a cool and dry place. Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

| Product Description | Pack size | Product code | Box quantity | EAN Code |
|-----------------------------|-----------|--------------|--------------|-----------------|
| Stucco Rapido Riparatutto – | | | | |
| Unistop in blister pack | 55 g | 57 031 001 | 16 | 8 005860 570313 |
| Stucco Rapido Riparatutto – | | | | |
| Unistop in roller | 55 g | 57 048 001 | 12 | 8 005860 570481 |



06/12/2013, 1th Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.