Via Edison, 76 - 20090 Trezzano sul Naviglio (MILANO) - ITALY TEL. +39.02.445731 - www.saratoga.it

Saratoga American Tape Technical Data Sheet

Saratoga American Tape is a polyester cloth carrier, laminated and coextruded with natural rubber adhesivized polyethylene tape. It is a high adhesiveness tape, waterproof, with excellent resistance to temperatures and atmospheric agents.

APPLICATION FIELDS

Sealing tape for plant engineering and heating and air-conditioning systems maintenance, for its features it has become essential in environments and activities completely different between them: work, manufacturing, office, house and Do-It-Yourself.

It is used on air ducts, pipelines, vacuum cleaner tubes, to repair garden pipes, to fix cables and panels on television shooting and exhibition stands, for small fixings/fastenings on cars and motorcycles (as first intervention), fixing helmets, boots, tennis rackets adornments and on many other uses.

It is a tape with a great mechanical strength, high adhesiveness on every surface (even on polythene foil), waterproof, smooth, adaptable, resistant to temperatures (up to 85°C) and atmosferic factors, easy to use (can be easily broken with hands).

APPLICATION AND INSTRUCTIONS

- · Unroll and apply the tape on clean, dry and degreased surfaces.
- Do not touch the tape with fingers (it would reduce its adhesive power).

Specific data			
Total thickness	0,26 mm (DIN EN 1942)		
Tensile strength	≥80 N/25 mm (DIN EN 14410)		
Elongation at break	From 5 to 10% (DIN EN 14410)		
Adhesion	≥8 N/25 mm (DIN EN 1939)		
Application temperature	+5 / +40°C		
Heat resistance	-20 / +85°C		

STORAGE AND SHELF LIFE

Between +20 and +25°C its shelf life is 24 months since manufacturing date.

CAUTIONS

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Box quantity	EAN Code
Blister pack mm 50	25 m	63 055 001	24	8 005860 630550
Roll mm 50	50 m	63 050 001	24	8 005860 630505
Unpackaged roll mm 50	25 m	63 054 001	24	8 005860 630543
Roll mm 50 x 25 m in palbox	80 pcs	63 056 001	1	8 005860 630550
Unpackaged black roll mm 38	10 m	63 053 001	36	8 005860 630536
Unpackaged black roll mm 50	25 m	63 054 002	24	8 005860 990289
Unpackaged white roll mm 50	25 m	63 054 003	24	8 005860 897120



07/27/2016, 2nd Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.