



Safety Data Sheet dated 8/4/2016, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: HAPPY COLOR MICACEO

Trade code: 88178?

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Spray painting decorative household, industrial and professional

1.3. Details of the supplier of the safety data sheet

Company:

SARATOGA INT. SFORZA SPA Via Edison 76 20090 Trezzano s/Naviglio (MI)

Tel. +039 02 445731 Fax +039 02 4452742

Competent person responsible for the safety data sheet:

trading@saratogasforza.com

1.4. Emergency telephone number

CAV - Ospedale Pediatrico "Bambino Gesù" - Roma - Tel. +39 06 68593726 (h24)

CAV - Azienda Ospedaliero-Universitaria Foggia - Foggia - Tel. +39 0881 732326 (h24)

CAV - Azienda Ospedaliera "A. Cardarelli" - Napoli - Tel. +39 081 7472870 (h24)

CAV - Policlinico "Umberto I" - Roma - Tel. +39 06 4450618 (h24)

CAV - Policlinico "A. Gemelli" - Roma - Tel. +39 06 3054343 (h24)

CAV - Azienda Ospedaliera "Careggi" U.O. Tossicologia Medica - Firenze - Tel. +39 055 7947819(h24)

CAV - Centro Nazionale di Informazione Tossicologica - Pavia - Tel. +39 0382 24444 (h24)


CAV - Ospedale "Niguarda Ca' Granda" - Milano - Tel. +39 02 66101029 (h24)

CAV - Azienda Ospedaliera "Papa Giovanni XXIII" - Bergamo - Tel. +39 800 883300 (h24)


SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

 Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

 Warning, Eye Irrit. 2, Causes serious eye irritation.

 Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Symbols:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Safety Data Sheet

HAPPY COLOR MICACEO

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 oC/122oF.
 P501 Dispose of contents / container to authorized centers.

The formation of explosive mixture is possible in insufficiently ventilated environments

Special Provisions:

None

Contents:

methyl acetate

n-butyl acetate

Special provisions according to Annex XVII of REACH and subsequent amendments:

Restricted to professional users.

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards










SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.










3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 30% - < 40%	methyl acetate	Index number: 607-021-00-X CAS: 79-20-9 EC: 201-185-2 REACH No.: 01-21194592 11-47-XXXX	 2.6/2 Flam. Liq. 2 H225  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336 EUH066
>= 15% - < 20%	propane	Index number: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	 2.2/1 Flam. Gas 1 H220
>= 12.5% - < 15%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1	 2.6/3 Flam. Liq. 3 H226  3.8/3 STOT SE 3 H336 EUH066
>= 7% - < 10%	butane	Index number: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	2.3/3 Aerosols 3 H229  2.2/1 Flam. Gas 1 H220
>= 3% - < 5%	and isobutane	Index number: 601-004-00-0 CAS: 75-28-5 EC: 200-857-2	 2.2/1 Flam. Gas 1 H220
>= 1% -	methanol	Index number: 603-001-00-X	 2.6/2 Flam. Liq. 2 H225

Safety Data Sheet

HAPPY COLOR MICACEO

< 3%		number: CAS: 67-56-1 EC: 200-659-6 REACH No.: 01-21194333 07-44-XXXX	 3.1/3/Dermal Acute Tox. 3 H311  3.1/3/Inhal Acute Tox. 3 H331  3.1/3/Oral Acute Tox. 3 H301  3.8/1 STOT SE 1 H370
>= 0.5% - < 1%	2-butoxyethanol; ethylene glycol monobutyl ether	Index number: CAS: 111-76-2 EC: 203-905-0 REACH No.: 01-21194751 08-36-XXXX	 3.1/4/Dermal Acute Tox. 4 H312  3.1/4/Inhal Acute Tox. 4 H332  3.1/4/Oral Acute Tox. 4 H302  3.2/2 Skin Irrit. 2 H315  3.3/2 Eye Irrit. 2 H319

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Safety Data Sheet

HAPPY COLOR MICACEO

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methyl acetate - CAS: 79-20-9

ACGIH - LTE(8h): 200 ppm - STE: 250 ppm - Notes: Headache, dizziness, nausea, eye dam (degeneration of ganglion cells in the retina)

Safety Data Sheet

HAPPY COLOR MICACEO

propane - CAS: 74-98-6
 TLV TWA - 1000 ppm - 0 mg/m³
 VLE short - 1000 ppm
 n-butyl acetate - CAS: 123-86-4
 ACGIH - LTE(8h): 150 ppm - STE: 200 ppm - Notes: Eye and URT irr
 butane - CAS: 106-97-8
 ACGIH - STE: 1000 ppm - Notes: CNS impair
 and isobutane - CAS: 75-28-5
 ACGIH - STE: 1000 ppm - Notes: CNS impair
 VLE short - 1000 ppm
 methanol - CAS: 67-56-1
 EU - LTE(8h): 260 mg/m³, 200 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)
 ACGIH - LTE(8h): 200 ppm - STE: 250 ppm - Notes: Skin BEI - Headache, eye dam, dizziness, nausea
 2-butoxyethanol; ethylene glycol monobutyl ether - CAS: 111-76-2
 EU - LTE(8h): 98 mg/m³, 20 ppm - STE: 246 mg/m³, 50 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)
 ACGIH - LTE(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Liquid aspect (under pressure), various colours.		
	--	--	

Safety Data Sheet

HAPPY COLOR MICACEO

Odour:	Caracteristic of solvent	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	Inf. 0 ° C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	Extremely flammable	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	a 20°C - 4,0 bar a 50°C - 8,0 bar	--	--
Vapour density:	N.A.	--	--
Relative density:	0,75 - 0,80 g/ml	--	--
Solubility in water:	NO	--	--
Solubility in oil:	SI	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - Stable under normal conditions
- 10.2. Chemical stability
 - Stable under normal conditions
- 10.3. Possibility of hazardous reactions
 - None
- 10.4. Conditions to avoid
 - Stable under normal conditions.
- 10.5. Incompatible materials

Safety Data Sheet

HAPPY COLOR MICACEO

- Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

- 11.1. Information on toxicological effects
Toxicological information of the mixture:
N.A.
- Toxicological information of the main substances found in the mixture:
methyl acetate - CAS: 79-20-9
LD50 (RABBIT) ORAL: 3705 MG/KG
- methanol - CAS: 67-56-1
LD50 (RAT) ORAL SINGLE DOSE: 5628 MG/KG
LD50 (RABBIT) SKINSINGLE DOSE: 15800 MG/KG

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

- 12.1. Toxicity
Adopt good working practices, so that the product is not released into the environment.
N.A.
- 12.2. Persistence and degradability
None
N.A.
- 12.3. Bioaccumulative potential
N.A.
- 12.4. Mobility in soil
N.A.
- 12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Safety Data Sheet

HAPPY COLOR MICACEO

SECTION 14: Transport information

- 14.1. UN number
ADR-UN number: 1950
IATA-Un number: 1950
IMDG-Un number: 1950
- 14.2. UN proper shipping name
ADR-Shipping Name: *ENTER PROPER SHIPPING NAME*
ADR-Shipping Name: AEROSOL
IATA-Shipping Name: *ENTER PROPER SHIPPING NAME*
IATA-Technical name: AEROSOL
IMDG-Shipping Name: *ENTER PROPER SHIPPING NAME*
IMDG-Technical name: AEROSOL
- 14.3. Transport hazard class(es)
ADR-Class: 2 5F
IATA-Class: 2.1
IATA-Label: 2.1
IMDG-Class: 2
IMDG-Class: 2
- 14.4. Packing group
ADR-Packing Group: -
IATA-Packing group: -
- 14.5. Environmental hazards
Marine pollutant: Marine pollutant
- 14.6. Special precautions for user
IATA-Passenger Aircraft: ----
IATA-Cargo Aircraft: 203
IMDG-Page: F-D, S-U
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
N.A.

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
None
- Volatile Organic compounds - VOCs = 615.00 g/l
Volatile CMR substances = 0.00 %
Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Safety Data Sheet

HAPPY COLOR MICACEO

Organic Carbon - C = 0.00

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Directive 2004/42/EC (VOC directive)

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):

N.A.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H229 Pressurized container: may burst if heated.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H301 Toxic if swallowed.

H370 Causes damage to organs.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H302 Harmful if swallowed.

H315 Causes skin irritation.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date.

It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

Safety Data Sheet

HAPPY COLOR MICACEO

GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.