OLIO SVITANTE

 cod.54127001
 Date of print: 28/09/2016

 Versione: 13/ EN
 Page 1 of 13
 Date of previous review: 18/05/2018

# SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code: 54127001
Product name. OLIO SVITANTE

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use. GREASE LUBRICANT FOR PROFESSIONAL USES

Uses advised against. THIS PRODUCT IS NOT RECOMMENDED FOR ALL THOSE INDUSTRIAL, PROFESSIONAL

OR CONSUMER USES NOT SPECIFICALLY IDENTIFIED ON THE LABEL.

Identified UsesIndustrial.Professional.Consumer.GENERAL USES--INDUSTRIAL MAINTENANCE--

1.3. Details of the supplier of the safety data sheet.

Name. SARATOGA INT. SFORZA SPA

Full address. VIA EDISON 76

District and Country. 20090 TREZZANO S/NAVIGLIO (MI)

ITALY

Tel. 0039.02.445731 Fax. 0039.02.4452742

e-mail address of the competent person.

responsible for the Safety Data Sheet.

Product distribution by:

trading@saratogasforza.com SARATOGA INT. SFORZA SPA

1.4. Emergency telephone number.

For urgent inquiries refer to. Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Cà Granda -Milano) (24h)

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia) Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo) Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze) Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma) Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma) Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)

### SECTION 2. Hazards identification.

### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1 H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

2.2. Label elements.

**OLIO SVITANTE** cod.54127001

Date of print: 28/09/2016 Date of previous review: 18/05/2018 Versione: 13/EN Page 2 of 13

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

Precautionary statements:

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F. P410+P412

P501 Dispose of contents / container to authorized collection centers.

### 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# **SECTION 3. Composition/information on ingredients.**

## 3.2. Mixtures.

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification. Classification 1272/2008 (CLP).

DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE

CAS. 64742-46-7  $50 \le x < 75$ Asp. Tox. 1 H304

CE. 920-107-4

INDEX. -

Nr. Reg. 01-2119453414-43

n-BUTANE

5 ≤ x < 15 Flam. Gas 1 H220, Note C U CAS. 106-97-8

EC. 203-448-7

INDEX. 601-004-00-0

Reg. no. 01-2119474691-32-xxxx

**OLIO SVITANTE** cod.54127001

Date of print: 28/09/2016 Date of previous review: 18/05/2018 Versione: 13/ EN Page 3 of 13

**CARBON DIOXIDE** 

Substance with a Community CAS. 124-38-9  $1 \le x < 5$ workplace exposure limit.

CE. 204-696-9

INDEX. -

**PROPAN** 

CAS. 74-98-6  $5 \le x < 15$ Flam. Gas 1 H220, Note U

EC. 200-827-9 INDEX. 601-003-00-5

Reg. no. 01-2119486944-21-xxxx

**IsoBUTANE** 

CAS. 75-28-5  $1 \le x < 5$ Flam. Gas 1 H220, Note C

EC. 200-857-2 INDEX. 601-004-00-0

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 23,90 %

## **SECTION 4. First aid measures.**

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

## 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## **SECTION 5. Firefighting measures.**

### 5.1. Extinguishing media.

# SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

OLIO SVITANTE cod.54127001 Versione: 13/ EN

Date of print: 28/09/2016
Page 4 of 13
Date of previous review: 18/05/2018

### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture.

### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

## 6.2. Environmental precautions.

Do not disperse in the environment.

## 6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage.**

### 7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

**OLIO SVITANTE** cod.54127001

Date of print: 28/09/2016 Versione: 13/ EN Date of previous review: 18/05/2018 Page 5 of 13

## 7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

## 7.3. Specific end use(s).

Information not available.

# SECTION 8. Exposure controls/personal protection.

## 8.1. Control parameters.

### Regulatory References:

BUTANE

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
	TLV-ACGIH	ACGIH 2016
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de
	3	protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição
		a agentes guímicos no trabalho - Diaro da Republica I 26; 2012-02-06
EU	OEL EU	Direttiva 2009/161/UE; Direttiva 2006/15/CE; Direttiva 2004/37/CE; Direttiva 2000/39/CE.
	TLV-ACGIH	ACGIH 2016

|--|

Threshold Limit Value. Country TWA/8h STEL/15min Туре

mg/m3 mg/m3 ppm ppm

TLV-ACGIH 1200 200

Health - Derived no-effect level - DNEL / DMEL

Effects on Effects on workers Acute local consumers. Chronic local Chronic Route of exposure Chronic Acute Acute local Acute systemic Chronic local systemic systemic systemic Inhalation. VND VND

- 1	DOTAIL					
	Threshold Limit Value.					
	Туре	Country	TWA/8h		STEL/15min	
			mg/m3	ppm	mg/m3	ppm
	AGW	DEU	2400	1000	9600	4000
	MAK	DEU	2400	1000	9600	4000
	VLA	ESP		800		
	VLEP	FRA	1900	800		
	WEL	GBR	1450	600	1810	750
	TLV	GRC	2350	1000		
	TLV-ACGIH				2377	1000

**OLIO SVITANTE** cod.54127001

Date of print: 28/09/2016 Date of previous review: 18/05/2018 Versione: 13/ EN Page 6 of 13

PROPAN Threshold Limit Value.					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	1800	1000	7200	4000
MAK	DEU	1800	1000	7200	4000
TLV	GRC	1800	1000		
TLV-ACGIH			1000		

CARBON DIOXIDE					
Threshold Limit Value.					
Туре	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	9100	5000	18200	10000
MAK	DEU	9100	5000	18200	10000
VLA	ESP	9150	5000		
WEL	GBR	9150	5000	27400	15000
TLV	GRC	9000	5000	54000	5000
VLEP	ITA	9000	5000		
VLE	PRT	9000	5000		
OEL	EU	9000	5000		
TLV-ACGIH		9000	5000	54000	30000

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

## 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

### HAND PROTECTION

None required.

### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

## **EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

## RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

## ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**OLIO SVITANTE** cod.54127001

Date of print: 28/09/2016 Date of previous review: 18/05/2018 Versione: 13/EN Page 7 of 13

## **SECTION 9. Physical and chemical properties.**

## 9.1. Information on basic physical and chemical properties.

Appearance aerosol Colour Pale yellow

caracteristic of solvent Odour

Odour threshold. Not defined Not available. Melting point / freezing point. < -15 °C. Initial boiling point. Not available. Boiling range. Not available. Flash point. Not available. Evaporation Rate Not available. Flammability of solids and gases flammable gas Lower inflammability limit. 0,89 % (V/V). Upper inflammability limit. 9,2 % (V/V). Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. 4320 mmHg Vapour density < 1 (Air =1)

Relative density. 0,716 Solubility soluble in organic solvents

Partition coefficient: n-octanol/water Not defined Auto-ignition temperature. > 270 °C. Not defined Decomposition temperature. > 23 cSt at 15°C Viscosity Explosive properties Not applicable Oxidising properties Not applicable

### 9.2. Other information.

24.00 % Total solids (250°C / 482°F)

76,00 % - 532,00 g/liter. 66,85 % - 454,58 g/liter VOC (Directive 2010/75/EC): g/liter VOC (volatile carbon):

## **SECTION 10. Stability and reactivity.**

## 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

**OLIO SVITANTE** cod.54127001

Date of print: 28/09/2016 Date of previous review: 18/05/2018 Versione: 13/ EN Page 8 of 13

10.4. Conditions to avoid.

Avoid overheating.

10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products.

Information not available

# **SECTION 11. Toxicological information.**

### 11.1. Information on toxicological effects.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component).

LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component).

LD50 (Oral) of the mixture: Not classified (no significant component)

LD50 (Dermal) of the mixture: Not classified (no significant component).

### DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE

LD50 (Oral).> 5000 mg/kg RAT (OCSE 401)

LD50 (Dermal). > 5000 mg/kg RABBIT ( OCSE 402)

LC50 (Inhalation).> 4591 mg/l RAT (OCSE403)

## SKIN CORROSION / IRRITATION.

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION.

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth.

**OLIO SVITANTE** cod.54127001

Date of print: 28/09/2016 Versione: 13/ EN Date of previous review: 18/05/2018 Page 9 of 13

# **SECTION 12. Ecological information.**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity.

DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE

EC50 - Crustacea. 1000 mg/l/48h (Daphnia Magna) (EL0) EC50 - Algae / Aquatic 1000 mg/l/72h (Oncorhyncus Mykiss)

Plants

1000 mg/l/96h (Pseudokirchneriella) (EL0) LC10 Fish.

### 12.2. Persistence and degradability.

BUTANE

Solubility in water. 0,1 - 100 mg/l

Rapidly biodegradable.

**PROPANE** 

Solubility in water. 0,1 - 100 mg/l

Rapidly biodegradable.

DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE

Biodegradability: Data not available.

## 12.3. Bioaccumulative potential.

**BUTANE** 

Partition coefficient: n-1.09

octanol/water.

**PROPANE** 

Partition coefficient: n-1,09

octanol/water.

### 12.4. Mobility in soil.

Information not available.

OLIO SVITANTE cod.54127001 Versione: 13/ EN

Date of print: 28/09/2016
Page 10 of 13
Date of previous review: 18/05/2018

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects.

Information not available.

## **SECTION 13. Disposal considerations.**

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information.**

#### 14.1. UN number.

ADR / RID, IMDG, 1950

IATA:

# 14.2. UN proper shipping name.

ADR / RID: AEROSOLS IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

### 14.3. Transport hazard class(es).

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



## 14.4. Packing group.

ADR / RID, IMDG,

IATA:

**OLIO SVITANTE** cod.54127001

Date of print: 28/09/2016 Date of previous review: 18/05/2018 Versione: 13/EN Page 11 of 13

14.5. Environmental hazards.

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user.

ADR / RID: HIN - Kemler: --Limited

Quantities: 1L restriction

code: (D)

Tunnel

Special Provision: -

IMDG: EMS: F-D, S-U Limited

Quantities: 1L

A802

Cargo:

Maximum quantity: 100Kg

Packaging instructions: 130

Pass.: Maximum quantity: 25Kg Packaging instructions:

130

Special Instructions:

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

# **SECTION 15. Regulatory information.**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

IATA:

Point. 40

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

**OLIO SVITANTE** cod.54127001

Date of print: 28/09/2016 Date of previous review: 18/05/2018 Versione: 13/ EN Page 12 of 13

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available

### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1 Flammable gas, category 1

Aerosol 1 Aerosol, category 1 Aerosol 3 Aerosol, category 3

Asp. Tox. 1 Aspiration hazard, category 1 H220 Extremely flammable gas. H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated. H304 May be fatal if swallowed and enters airways.

## LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- · GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**OLIO SVITANTE** cod.54127001 Versione: 13/ EN

Date of print: 28/09/2016 Date of previous review: 18/05/2018 Page 13 of 13

### GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 01 / 03 / 08.