LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN

Page 1 of 13

Date of print: 11/01/2019 Date of review: 28/09/2016

SECTION 1. Identification of t	he substance/mixture and of	f the company/undertaki	ng.	
1.1. Product identifier.				
Code: Product name.	54123001 - 54125001 LASER SPRAY			
Flouder hame.				
1.2. Relevant identified uses of the substance or mixture and uses advised against.      Intended use.    GREASE LUBRICANT - unloose, hydroextractor and antioxidant				
Uses advised against.	THIS PRODUCT IS NOT RECOMMEND IDENTIFIED ON THE LABEL.	DED FOR ALL THOSE USES NOT	SPECIFICALLY	
Identified Uses	Industrial.	Professional.	Consumer.	
GENERAL USES	-	-	~	
INDUSTRIAL MAINTENANCE	Ý	<b>v</b>	-	
<b>1.3. Details of the supplier of the safety o</b> Name. Full address. District and Country.	data sheet. SARATOGA INT. SFORZA SPA VIA EDISON 76 20090 TREZZANO S/NAVIGLIO (MI) ITALY Tel. 0039.02.445731 Fax. 0039.02.4452742			
e-mail address of the competent person.	Fax: 0039.02.4452742			
responsible for the Safety Data Sheet.	trading@saratogasforza.com			
responsible for the Safety Data Sheet.	traunig@saratogasioiza.com			
<b>1.4. Emergency telephone number.</b> For urgent inquiries refer to.CAV - Ospedale Pediatrico "Bambino Gesù" - Roma - Tel. +39 06 68593726 (h24) CAV - Azienda Ospedaliero-Universitaria Foggia - Foggia - Tel. +39 0881 732326 (h24) CAV - Azienda Ospedaliera "A. Cardarelli" - Napoli - Tel. +39 081 7472870 (h24) CAV - Policlinico "Umberto I" - Roma - Tel. +39 06 4450618 (h24) CAV - Policlinico "A. Gemelli" - Roma - Tel. +39 06 3054343 (h24) CAV - Azienda Ospedaliera "Careggi" U.O. Tossicologia Medica - Firenze - Tel. +39 055 7947819(h24) CAV - Centro Nazionale di Informazione Tossicologica - Pavia - Tel. +39 0382 24444 (h24) CAV - Ospedale "Niguarda Ca' Granda" - Milano - Tel. +39 02 66101029 (h24) CAV - Azienda Ospedaliera "Papa Giovanni XXIII" - Bergamo - Tel. +39 800 883300 (h24)				
SECTION 2. Hazards identific	ation.			
2.1. Classification of the substance or mixture.				

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.

2.2. Label elements.

LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN

Page 2 of 13

Date of print: 11/01/2019 Date of review: 28/09/2016

		· · · · · · · · · · · · · · · · · · ·	
azard labelling pursuant	to EC Regulation 1272/2008 (CLP) and s	subsequent amendments and supplements.	
Hazard pictograms:			
$\checkmark$			
Signal words:	Danger		
lazard statements:			
H222 H229	Extremely flammable aerosol. Pressurised container: may burst if he	eated.	
EUH066	Repeated exposure may cause skin di	ryness or cracking.	
Precautionary statements			
P101	If medical advice is needed, have prod	duct container or label at hand.	
P102 P210	Keep out of reach of children.	parks, open flames and other ignition source	as No smoking
P211	Do not spray on an open flame or othe		s. No shoking.
P251	Do not pierce or burn, even after use.		
P271 P410+P412	Use only outdoors or in a well-ventilate Protect from sunlight. Do no expose to	ed area. temperatures exceeding 50°C / 122°F.	
P501	Dispose of contents / container to auth		
2.3. Other hazards.			
	data, the product does not contain any PE	3T or vPvB in percentage greater than 0,1%	
On the basis of available o	data, the product does not contain any PE		
On the basis of available o			
On the basis of available on SECTION 3. Con			
On the basis of available of SECTION 3. Con 3.2. Mixtures. Contains:		sheet.	
On the basis of available of SECTION 3. Con 3.2. Mixtures. Contains: The full wording of hazard Identification.	position/information on ing	redients.	
On the basis of available of SECTION 3. Con 3.2. Mixtures. Contains: The full wording of hazard Identification.	(H) phrases is given in section 16 of the	sheet. Classification 1272/2008 (CLP).	
On the basis of available of SECTION 3. Con 3.2. Mixtures. Contains: The full wording of hazard Identification. DISTILLATES (PETRO	(H) phrases is given in section 16 of the LEUM), HYDROTREATED MIDDLE	sheet. Classification 1272/2008 (CLP).	
On the basis of available of SECTION 3. Con 3.2. Mixtures. Contains: The full wording of hazard Identification. DISTILLATES (PETRO) CAS. 64742-46-7	(H) phrases is given in section 16 of the LEUM), HYDROTREATED MIDDLE	sheet. Classification 1272/2008 (CLP).	
On the basis of available of <b>SECTION 3. Con</b> <b>3.2. Mixtures.</b> Contains: The full wording of hazard Identification. <b>DISTILLATES (PETRO</b> ) CAS. 64742-46-7 CE. 920-107-4	(H) phrases is given in section 16 of the EUM), HYDROTREATED MIDDLE 50 ≤ x < 7	sheet. Classification 1272/2008 (CLP).	
On the basis of available of SECTION 3. Con 3.2. Mixtures. Contains: The full wording of hazard Identification. DISTILLATES (PETRO) CAS. 64742-46-7 CE. 920-107-4 INDEX	(H) phrases is given in section 16 of the EUM), HYDROTREATED MIDDLE 50 ≤ x < 7	sheet. Classification 1272/2008 (CLP).	
On the basis of available of SECTION 3. Con 3.2. Mixtures. Contains: The full wording of hazard Identification. DISTILLATES (PETRO) CAS. 64742-46-7 CE. 920-107-4 INDEX Nr. Reg. 01-21194534	(H) phrases is given in section 16 of the EUM), HYDROTREATED MIDDLE 50 ≤ x < 7	sheet. Classification 1272/2008 (CLP). 75 Asp. Tox. 1 H304	
On the basis of available of <b>SECTION 3. Con</b> <b>3.2. Mixtures.</b> Contains: The full wording of hazard Identification. <b>DISTILLATES (PETRON</b> CAS. 64742-46-7 CE. 920-107-4 INDEX Nr. Reg. 01-21194534 <b>n-BUTANE</b>	(H) phrases is given in section 16 of the <b>LEUM), HYDROTREATED MIDDLE</b> $50 \le x < 7$	sheet. Classification 1272/2008 (CLP). 75 Asp. Tox. 1 H304	
On the basis of available of <b>SECTION 3. Con</b> <b>3.2. Mixtures.</b> Contains: The full wording of hazard Identification. <b>DISTILLATES (PETRO)</b> CAS. 64742-46-7 CE. 920-107-4 INDEX Nr. Reg. 01-21194534 <b>n-BUTANE</b> CAS. 106-97-8	(H) phrases is given in section 16 of the <b>LEUM), HYDROTREATED MIDDLE</b> $50 \le x < 7$	sheet. Classification 1272/2008 (CLP). 75 Asp. Tox. 1 H304	
On the basis of available of SECTION 3. Con 3.2. Mixtures. Contains: The full wording of hazard Identification. DISTILLATES (PETRO) CAS. 64742-46-7 CE. 920-107-4 INDEX Nr. Reg. 01-21194534 n-BUTANE CAS. 106-97-8 EC. 203-448-7	(H) phrases is given in section 16 of the <b>LEUM), HYDROTREATED MIDDLE</b> $50 \le x < 7$ 14-43 $5 \le x < 15$	sheet. Classification 1272/2008 (CLP). 75 Asp. Tox. 1 H304	

LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN	Page	3 of 13	Date of print: 11/01/2019 Date of review: 28/09/2016
PROPAN			
CAS. 74-98-6	5≤x< 15	Flam. Gas 1 H220, Note U	
EC. 200-827-9			
INDEX. 601-003-00-5			
Reg. no. 01-2119486944-21-xxxx			
CARBON DIOXIDE			
CAS. 124-38-9	1 ≤ x < 5	Substance with a Community workplace exposure limit.	
CE. 204-696-9			
INDEX			
IsoBUTANE			
CAS. 75-28-5			
EC. 200-857-2	1≤x< 5	Flam. Gas 1 H220, Note C	
INDEX. 601-004-00-0			
Reg. no. 1-2119485395-27-xxxx			

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 23,90 %

# **SECTION 4. First aid measures.**

#### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

# **SECTION 5. Firefighting measures.**

### 5.1. Extinguishing media.

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN

Page 4 of 13

Date of print: 11/01/2019 Date of review: 28/09/2016

UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

#### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

#### 5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6.** Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

#### 6.2. Environmental precautions.

Do not disperse in the environment.

#### 6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage.**

#### 7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN

Page 5 of 13

Date of print: 11/01/2019 Date of review: 28/09/2016

7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

## 7.3. Specific end use(s).

Information not available.

# **SECTION 8. Exposure controls/personal protection.**

### 8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte nº 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06
EU	OEL EU TLV-ACGIH	Direttiva 2009/161/UE; Direttiva 2006/15/CE; Direttiva 2004/37/CE; Direttiva 2000/39/CE. ACGIH 2016

DISTILLATES (PETROLEU	M), HYDROTRE	EATED MIDDLE						
Threshold Limit Value.	0	704/0/01						
Туре	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
TLV-ACGIH		1200	200					
Health - Derived no-effect	level - DNEL / D	MEL						
	Effects on consumers.				Effects on workers			- · ·
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation.	VND	VND						

Threshold Limit Value.
Type Country TWA/8h STEL/15min
mg/m3 ppm mg/m3 ppm
AGW DEU 2400 1000 9600 4000
MAK DEU 2400 1000 9600 4000
VLA ESP 800
VLEP FRA 1900 800
WEL GBR 1450 600 1810 750
TLV GRC 2350 1000
TLV-ACGIH 2377 1000

LASER SPRAY						
cod.54123001-54125001 Revision: 13.2/ EN			Page 6 d	of 13		Date of print: 11/01/2019 Date of review: 28/09/2016
			0			
PROPAN Threshold Limit Value.						
Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
TLV	GRC	1800	1000			
TLV-ACGIH			1000			
CARBON DIOXIDE						
Threshold Limit Value.	Country	TWA/8h		STEL/15min		
1 ypc	Country	mg/m3	ppm	mg/m3	ppm	
AGW	DEU	9100	5000	18200	10000	
MAK	DEU	9100	5000	18200	10000	
VLA	ESP	9150	5000	10200	10000	
WEL	GBR	9150	5000	27400	15000	
TLV	GRC	9000	5000	54000	5000	
VLEP	ITA	9000	5000	34000	5000	
VLE	PRT	9000	5000			
OEL	EU	9000	5000			
TLV-ACGIH	20	9000	5000	54000	30000	
				0.000		
Legend:						
	–	5505			-	
(C) = CEILING ; INHAL =	Innalable Fracti	on ; RESP =	Respirable Fra	ction ; THORA	= Inoracic Fraction.	
8.2. Exposure controls.						
As the use of adequate tech through effective local aspirat						sure that the workplace is well aired applicable standards.
HAND PROTECTION None required.						
SKIN PROTECTION Wear category I professional and water after removing prot	long-sleeved o ective clothing.	veralls and safe	ty footwear (se	ee Directive 89/68	6/EEC and standard E	EN ISO 20344). Wash body with soap
EYE PROTECTION	oo (ooo otondor					

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387). Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold

values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN

Page 7 of 13

Date of print: 11/01/2019 Date of review: 28/09/2016

# **SECTION 9.** Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Odour threshold.NopH.NoMelting point / freezing point.< -Initial boiling point.NoBoiling range.NoFlash point.NoEvaporation RateNoFlammability of solids and gasesflanLower inflammability limit.0,8Upper inflammability limit.9,2Lower explosive limit.NoVapour pressure.324Vapour density< 1Relative density.0,6SolubilitysolPartition coefficient: n-octanol/waterNoAuto-ignition temperature.> 2Decomposition temperature.> 2Explosive propertiesNo	aracteristic of solvent ot defined ot available. -15 °C. ot available. ot available. ot available. ot available. ot available. ammable gas 89 % (V/V). 2 % (V/V). ot available. ot available. 260 mmHg 1 (Air = 1) 68 Juble in organic solvents ot defined 270 °C. ot defined 23 cSt at 15°C ot applicable ot applicable
--	---

## 9.2. Other information.

Total solids (250°C / 482°F)	24,00 %			
VOC (Directive 2010/75/EC) :	76,00 %	-	532,00	g/liter.
VOC (volatile carbon) :	66,85 %	-	454,58	g/liter

# **SECTION 10. Stability and reactivity.**

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN

Page 8 of 13

Date of print: 11/01/2019 Date of review: 28/09/2016

10.4. Conditions to avoid.

Avoid overheating.

10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products.

Information not available.

# **SECTION 11. Toxicological information.**

11.1. Information on toxicological effects.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:Not classified (no significant component). LC50 (Inhalation - mists / powders) of the mixture:Not classified (no significant component). LD50 (Oral) of the mixture:Not classified (no significant component). LD50 (Dermal) of the mixture:Not classified (no significant component). DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE LD50 (Oral).> 5000 mg/kg RAT (OCSE 401)

LD50 (Dermal).> 5000 mg/kg RABBIT ( OCSE 402)

LC50 (Inhalation).> 4591 mg/l RAT (OCSE403)

SKIN CORROSION / IRRITATION.

Does not meet the classification criteria for this hazard class. SERIOUS EYE DAMAGE / IRRITATION.

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class. GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class. CARCINOGENICITY.

Does not meet the classification criteria for this hazard class. REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class. STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class. ASPIRATION HAZARD.

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth.

LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN

Page 9 of 13

Date of print: 11/01/2019 Date of review: 28/09/2016

# **SECTION 12. Ecological information.**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity.	
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE	
EC50 - Crustacea.	1000 mg/l/48h (Daphnia Magna) (EL0)
EC50 - Algae / Aquatic Plants.	1000 mg/l/72h (Oncorhyncus Mykiss)
LC10 Fish.	1000 mg/l/96h (Pseudokirchneriella) (EL0)
12.2. Persistence and degradability.	
BUTANE	
Solubility in water.	0,1 - 100 mg/l
Rapidly biodegradable.	
PROPANE	
Solubility in water.	0,1 - 100 mg/l
Rapidly biodegradable.	
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE	
Biodegradability: Data not available.	
12.3. Bioaccumulative potential.	
BUTANE	
Partition coefficient: n- octanol/water.	1,09
PROPANE	
Partition coefficient: n- octanol/water.	1,09
12.4. Mobility in soil.	
Information not available.	

LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN

Page 10 of 13

Date of print: 11/01/2019 Date of review: 28/09/2016

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects.

Information not available.

# **SECTION 13. Disposal considerations.**

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information.**

#### 14.1. UN number.

ADR / RID, IMDG, 1950 IATA:

#### 14.2. UN proper shipping name.

ADR / RID:	AEROSOLS
IMDG:	AEROSOLS
IATA:	AEROSOLS, FLAMMABLE

### 14.3. Transport hazard class(es).

ADR / RID:	Class: 2	Label: 2.1
IMDG:	Class: 2	Label: 2.1
IATA:	Class: 2	Label: 2.1



## 14.4. Packing group.

ADR / RID, IMDG, IATA:

		in accordance with Regulation	(CE) Num. 1907/2000	
LASER SPRA cod.54123001- Revision: 13.2/	-54125001	Page 11 of 13		Date of print: 11/01/2019 Date of review: 28/09/2016
14.5. Environmen	ital hazards.			
ADR / RID:	NO			
IMDG:	NO			
IATA:	NO			
14.6. Special pred	cautions for user			
ADR / RID:		HIN - Kemler:	Limited Quantities: 1L	Tunnel restriction code: (D)
		Special Provision: -		
IMDG:		EMS: F-D, S-U	Limited Quantities: 1L	
IATA:		Cargo:	Maximum quantity: 100Kg	Packaging instructions: 130
		Pass.:	Maximum quantity: 25Kg	Packaging instructions:
		Special Instructions:	A802	130
14.7. Transport ir	n bulk according	to Annex II of Marpol and the IBC Code.		
Information not rel	evant.			
SECTION 4	5 Regulator	vinformation		
SECTION 15. Regulatory information.				

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point. 40

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN

Page 12 of 13

Date of print: 11/01/2019 Date of review: 28/09/2016

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Asp. Tox. 1	Aspiration hazard, category 1
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H304	May be fatal if swallowed and enters airways.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

LASER SPRAY cod.54123001-54125001 Revision: 13.2/ EN

Page 13 of 13

Date of print: 11/01/2019 Date of review: 28/09/2016

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- Regulation (EU) 2015/830 of the European Parliament 4
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 (isobutane registration number).