RIVELATORE FUGHE GAS

 cod. 54144001
 Date of print: 07/04/2020

 Revision: 13 / EN
 Page 1 of 12
 Date of review: 28/09/2016

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code: **54144001**

Product name. RIVELATORE FUGHE GAS

1.2. Relevant identified uses of the substance or mixture and uses advised against.

1.3. Details of the supplier of the safety data sheet.

Name. SARATOGA INT. SFORZA SPA

Full address. Via Edison 76

District and Country. 20090 Trezzano s/Naviglio (MI)

ITALIA

Tel. +39-02 445731 Fax +39-02 4452742

e-mail address of the competent person.

responsible for the Safety Data Sheet. trading@saratogasforza.com

1.4. Emergency telephone number.

For urgent inquiries refer to. CAV - Ospedale Pediatrico "Bambino Gesù" - Roma - Tel. +39 06 68593726 (h24)

CAV - Azienda Ospedaliero-Universitaria Foggia - Foggia - Tel. +39 0881 732326 (h24)

CAV - Azienda Ospedaliera "A. Cardarelli" - Napoli - Tel. +39 081 7472870 (h24)

CAV - Policlinico "Umberto I" - Roma - Tel. +39 06 4450618 (h24) CAV - Policlinico "A. Gemelli" - Roma - Tel. +39 06 3054343 (h24)

CAV - Azienda Ospedaliera "Careggi" U.O. Tossicologia Medica - Firenze - Tel. +39 055

7947819(h)h224

CAV - Centro Nazionale di Informazione Tossicologica - Pavia - Tel. +39 0382 24444 (h24)

CAV - Ospedale "Niguarda Ca' Granda" - Milano - Tel. +39 02 66101029 (h24)

CAV - Azienda Ospedaliera "Papa Giovanni XXIII" - Bergamo - Tel. +39 800 883300 (h24)

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 2 H223 Flammable aerosol.

H229 Pressurized container: may burst if heated.

RIVELATORE FUGHE GAS

 cod. 54144001
 Date of print: 07/04/2020

 Revision: 13 / EN
 Page 2 of 12
 Date of review: 28/09/2016

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Caution

Hazard statements:

H223 Flammable aerosol.

H229 Pressurized container: may burst if heated.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.

P501 Dispose of contents / container in authorized collection centers.

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.2. Mixtures.

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification. Classification 1272/2008 (CLP).

DME - DIMETHYLETHER

CAS. 115-10-6 5 ≤ x < 15 Flam. Gas 1 H220, Note U

EC. 204-065-8 INDEX. 603-019-00-8

Reg. no. 01-2119472128-37-xxxx

RIVELATORE FUGHE GAS

 cod. 54144001
 Date of print: 07/04/2020

 Revision: 13 / EN
 Page 3 of 12
 Date of review: 28/09/2016

SODIUM N-LAUROYLSARCOSINATE SOL 30%

CAS. 137-16-6 1 ≤ x < 5 Acute Tox. 4 H332, Eye Irrit. 2 H319

EC. 205-281-5 INDEX. -

Reg. no. 01-2119527780-39-0001

SODIUM NITRITE

CAS. 7632-00-0 0 ≤ x < 1 Ox. Sol. 2 H272, Acute Tox. 3 H301, Aquatic Acute 1 H400 M=1

EC. 231-555-9 INDEX. 007-010-00-4

Reg. no. 01-2119471836-27-0000

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 13,90 %

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

RIVELATORE FUGHE GAS

 cod. 54144001
 Date of print: 07/04/2020

 Revision: 13 / EN
 Page 4 of 12
 Date of review: 28/09/2016

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions.

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

RIVELATORE FUGHE GAS

 cod. 54144001
 Date of print: 07/04/2020

 Revision: 13 / EN
 Page 5 of 12
 Date of review: 28/09/2016

7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

Storage class TRGS 510 (Germany):

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Information not available

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type B filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance liquid Colour opalescent

RIVELATORE FUGHE GAS

cod. 54144001 Date of print: 07/04/2020 Revision: 13 / EN Page 6 of 12 Date of review: 28/09/2016

Odour no odour Odour threshold. Non definita 8,4 . Melting point / freezing point. < 2 °C. Initial boiling point. Not available. Boiling range. Not available. Flash point. Not available. Evaporation Rate Non definito Flammability of solids and gases flammable gas Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. 3 % (V/V). 19 % (V/V). Upper explosive limit. Vapour pressure. Not available. Vapour density Non definita 0,93 Relative density. Solubility soluble in water

Solublity soluble in water
Partition coefficient: n-octanol/water Non definito
Auto-ignition temperature. > 300 °C.
Decomposition temperature. Non definita
Viscosity Not available.
Explosive properties not applicable
Oxidising properties not applicable

9.2. Other information.

Total solids (250°C / 482°F) 100,00 % VOC (Directive 2010/75/EC) : 0 VOC (volatile carbon) : 0

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

RIVELATORE FUGHE GAS

 cod. 54144001
 Date of print: 07/04/2020

 Revision: 13 / EN
 Page 7 of 12
 Date of review: 28/09/2016

Avoid overheating.

10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:> 20 mg/l

LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component).

LD50 (Oral) of the mixture:>2000 mg/kg

LD50 (Dermal) of the mixture:Not classified (no significant component).

SODIUM NITRITE

LD50 (Oral).180 mg/kg Rat

SKIN CORROSION / IRRITATION.

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION.

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class. CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information.

RIVELATORE FUGHE GAS

 cod. 54144001
 Date of print: 07/04/2020

 Revision: 13 / EN
 Page 8 of 12
 Date of review: 28/09/2016

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity.

SODIUM NITRITE

LC50 - for Fish.
 EC50 - for Crustacea.
 EC50 - for Algae / Aquatic Plants.
 O,79 mg/l/96h Oncorhynchus mykiss
 23,31 mg/l/48h Penaeus monodon
 159 mg/l/72h Tetraseimis chui

12.2. Persistence and degradability.

SODIOLAUROIL SARCOSINATO SOL

30%

Rapidly biodegradable.

SODIUM NITRITE

Solubility in water. 848000 mg/l

Biodegradability: Information not available.

12.3. Bioaccumulative potential.

SODIUM NITRITE

Partition coefficient: n-octanol/water. -3,7

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

RIVELATORE FUGHE GAS

 cod. 54144001
 Date of print: 07/04/2020

 Revision: 13 / EN
 Page 9 of 12
 Date of review: 28/09/2016

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG,

1950

IATA:

14.2. UN proper shipping name.

ADR / RID: AEROSOLS IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es).

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1

14.4. Packing group.

ADR / RID, IMDG, IATA:

14.5. Environmental hazards.

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user.

ADR / RID: HIN - Kemler: -- Limited Quantities: 1 L Tunnel restriction code: (D)

Special Provision: -

IMDG: EMS: F-D, S-U Limited Quantities: 1 L

IATA: Cargo: Maximum quantity: 100 Kg Packaging instructions: 130

Pass.: Maximum quantity: 25 Kg Packaging instructions: 130

RIVELATORE FUGHE GAS cod. 54144001

 cod. 54144001
 Date of print: 07/04/2020

 Revision: 13 / EN
 Page 10 of 12
 Date of review: 28/09/2016

Special Instructions: A802

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point.

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

40

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

RIVELATORE FUGHE GAS

cod. 54144001 Date of print: 07/04/2020 Revision: 13 / EN Page 11 of 12 Date of review: 28/09/2016

Flam. Gas 1 Flammable gas, category 1
Ox. Sol. 2 Oxidising solid, category 2
Acute Tox. 3 Acute toxicity, category 3
Acute Tox. 4 Eye Irrit. 2 Eye irritation, category 2

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

H220 Extremely flammable gas.H272 May intensify fire; oxidiser.

H301 Toxic if swallowed.H332 Harmful if inhaled.

H319 Causes serious eye irritation. H400 Very toxic to aquatic life.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

RIVELATORE FUGHE GAS

cod. 54144001 Date of print: 07/04/2020 Date of review: 28/09/2016 Revision: 13 / EN Page 12 of 12

10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament - The Merck Index. - 10th Edition

- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified: