LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN	Page 1 of 14		Date of print: 13/05/2020 Date of review: 28/09/2016
SECTION 1. Identification of the sub	stance/mixture and of th	e company/underta	ikina.
			5
1.1. Product identifier. Code:	54262001		
Product name.	LUBRIFICANTE ARMI		
1.2. Relevant identified uses of the substance or n Intended use.	nixture and uses advised against SPECIAL LUBRICANT FOR AR		
Identified Uses	Industrial.	Professional.	Consumer.
GENEARL CONSUMER	-	-	4
PROFESSIONAL MAINTENANCE	4	4	-
Uses advised against	This product is not recommen label.	ded for all those uses not s	pecifically identified on the
1.3. Details of the supplier of the safety data sheet	•		
Name.	SARATOGA INT. SFORZA SPA		
Full address. District and Country.	Via Edison 76 20090 Trezzano s/Naviglio (MI)		
	ITALIA		
	Tel. +39-02 445731		
	Fax +39-02 4452742		
e-mail address of the competent person.			
responsible for the Safety Data Sheet.	trading@saratogasforza.com		
1.4. Emergency telephone number.			
For urgent inquiries refer to.	CAV - Ospedale Pediatrico "Ba CAV - Azienda Ospedaliero-Un CAV - Azienda Ospedaliera "A. CAV - Policlinico "Umberto I" - CAV - Policlinico "A. Gemelli" CAV - Azienda Ospedaliera "Ca 7947819 (h24) CAV - Centro Nazionale di Infor CAV - Ospedale "Niguarda Ca' CAV - Azienda Ospedaliera "Pa	iversitaria Foggia - Foggia Cardarelli" - Napoli - Tel. + Roma - Tel. +39 06 4450618 Roma - Tel. +39 06 305434 areggi" U.O. Tossicologia N rmazione Tossicologica - P Granda" - Milano - Tel. +39	- Tel. +39 0881 732326 (h24) 39 081 7472870 (h24) 3 (h24) 3 (h24) ledica - Firenze - Tel. +39 055 avia - Tel. +39 0382 24444 (h24) 02 66101029 (h24)
SECTION 2. Hazards identification.			

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

		•	, , , ,	
LUBRIFICANTE ARMI cod. 54262001				Date of print: 13/05/2020
Revision: 13 / EN		Page 2 of	14	Date of review: 28/09/2016
lazard classification and in	dication:	11000		
Aerosol, category 1		H222 H229	Extremely flammable aeros Pressurised container: may	
Hazardous to the aquatic	environment, chronic toxicity,	H412	Harmful to aquatic life with	
category 3	environment, enrenie texicity,	11712		
2.2. Label elemente				
2.2. Label elements.				
lazard labelling pursuant to	EC Regulation 1272/2008 (CLF) and subsequent a	mendments and supplements.	
I lower and a lot a surgery set				
Hazard pictograms:				
•				
Signal words:	Danger			
lement statements.				
lazard statements:				
H222	Extremely flammable aerosol.			
H229 H412	Pressurized container: may burst if heated. Harmful to aquatic life with long lasting effects.			
		glading choole.		
Precautionary statements:				
P101	If medical advice is needed, ha	vo product containor	or label at hand	
P102	Keep out of reach of children.		or laber at hand.	
P210			ames and other ignition sources. No	smoking.
P211 P251	Do not spray on an open flame Pressurized container: do not p	or other ignition sou	rce. after use.	
P271	Use only outdoors or in a well-	ventilated area.		
P273	Avoid release to the environme	ent.	a avaaading E0°C / 122°E	
P410+P412 P501	Protect from sunlight. Do no ex Dispose of contents and contain			
Product not intended for use	es provided for by Dir. 2004/42/C	E.		
2.3. Other hazards.				
On the basis of available da	ta, the product does not contain	any PBT or vPvB in	percentage greater than 0,1%.	
SECTION 3. Comp	oosition/information o	n ingredients.		
3.2. Mixtures.				
Contains:				

The full wording of hazard (H) phrases is given in section 16 of the sheet.

LUBRIFICANTE ARMI		
cod. 54262001	_	Date of print: 13/05/2020
Revision: 13 / EN	Pag	e 3 of 14 Date of review: 28/09/2016
Identification.		Classification 1272/2008 (CLP).
MINERAL OIL HYDROTREATYNG USP		
CAS. 8042-47-5	50 ≤ x < 75	Asp. Tox. 1 H304, Note P
EC. 232-455-8		
INDEX		
Reg. no. 01-2119487078-27		
BUTANE		
CAS. 106-97-8	15 ≤ x < 30	Flam. Gas 1 H220, Note C U
EC. 203-448-7		
INDEX. 601-004-00-0		
Reg. no. 01-2119474691-32-xxxx		
PROPANE		
CAS. 74-98-6	5≤x< 15	Flam. Gas 1 H220, Note U
EC. 200-827-9		
INDEX. 601-003-00-5		
Reg. no. 01-2119486944-21-xxxx		
NAFTA DI HYDROTREATING		
CAS. 64742-49-0	$2,5 \le x \le 5$	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411, Note P
EC. 265-151-9		
INDEX. 649-328-00-1		
Reg. no. 012119484651-34-XXXX		
ISOBUTANE		
CAS. 75-28-5	1≤x< 5	Flam. Gas 1 H220, Note C
EC. 200-857-2		
INDEX. 601-004-00-0		
Reg. no. 01-2119485395-27-xxxx		

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 37,70 %

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorized by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN

Page 4 of 14

Date of print: 13/05/2020 Date of review: 28/09/2016

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions.

Do not disperse in the environment.

LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN

Page 5 of 14

Date of print: 13/05/2020 Date of review: 28/09/2016

6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

Storage class TRGS 510 (Germany): 2B

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
	TLV-ACGIH	ACGIH 2016

BUTANE Threshold Limit Value. Туре Country

TWA/8h

STEL/15min

LUBRIFICANTE ARMI cod. 54262001 Date of print: 13/05/2020 Revision: 13 / EN Page 6 of 14 Date of review: 28/09/2016 mg/m3 mg/m3 ppm ppm AGW DEU 2400 1000 9600 4000 MAK DEU 2400 1000 9600 4000 ESP 800 VLA VLEP 1900 800 FRA WEL GBR 1450 600 1810 750 TLV GRC 2350 1000 TLV-ACGIH 2377 1000 PROPANE **Threshold Limit Value.** STEL/15min Type Country TWA/8h mg/m3 mg/m3 ppm ppm AGW DEU 1800 1000 7200 4000 MAK DEU 1800 1000 7200 4000 GRC TLV 1800 1000

Legend:

TLV-ACGIH

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

1000

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387). Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN

Page 7 of 14

Date of print: 13/05/2020 Date of review: 28/09/2016

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	aerosol
Colour	dark brown
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	$< -5 \degree$ C.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	Not available.
Evaporation Rate	Not available.
Flammability of solids and gases	flammable gas
Lower inflammability limit.	0,98 % (V/V).
Upper inflammability limit.	8,9 % (V/V).
Upper explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	4750 mmHg
Vapour density	< 1 (Aria=1)
Relative density.	0,76
Solubility	soluble in organic solvents
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	> 270 °C.
Decomposition temperature.	Non definita
Viscosity	> 68cSt a 15°C
Explosive properties	not applicable
Oxidising properties	not applicable

9.2. Other information.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN

Page 8 of 14

Date of print: 13/05/2020 Date of review: 28/09/2016

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

Avoid overheating.

10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:Not classified (no significant component).

LC50 (Inhalation - mists / powders) of the mixture:Not classified (no significant component).

LD50 (Oral) of the mixture:Not classified (no significant component).

LD50 (Dermal) of the mixture:Not classified (no significant component).

NAFTA DI HYDROTREATING LD50 (Oral).> 2000 mg/kg mouse LD50 (Dermal).> 2000 mg/kg mouse LC50 (Inhalation).> 20 mg/l mouse

MINERAL OIL LD50 (Oral).> 5000 mg/kg LD50 (Dermal).> 2000 mg/m3 LC50 (Inhalation).> 5000 mg/m3

SKIN CORROSION / IRRITATION. Does not meet the classification criteria for this hazard class. SERIOUS EYE DAMAGE / IRRITATION. Does not meet the classification criteria for this hazard class. RESPIRATORY OR SKIN SENSITISATION. Does not meet the classification criteria for this hazard class. GERM CELL MUTAGENICITY. Does not meet the classification criteria for this hazard class.

LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN

Page 9 of 14

Date of print: 13/05/2020 Date of review: 28/09/2016

CARCINOGENICITY. Does not meet the classification criteria for this hazard class. REPRODUCTIVE TOXICITY. Does not meet the classification criteria for this hazard class. STOT - SINGLE EXPOSURE. Does not meet the classification criteria for this hazard class. STOT - REPEATED EXPOSURE. Does not meet the classification criteria for this hazard class. ASPIRATION HAZARD. Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth.

SECTION 12. Ecological information.

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment. NAFTA DI HYDROTREATING Non immettere nelle acque freatiche, nei corsi d'acqua o nelle fognature.

12.1. Toxicity.

NAFTA DI HYDROTREATING Tossico per pesci. plancton e organismi acquatici.

NAFTA DI HYDROTREATING	
EC50 - for Crustacea.	55 mg/l/48h
EC50 - for Algae / Aquatic Plants.	30 mg/l/72h
MINERAL OIL	
LC50 - for Fish.	> 100 mg/l/96h pesce
EC50 - for Crustacea.	> 100 mg/l/48h Dafnia
12.2. Persistence and degradability.	
NAFTA DI HYDROTREATING Si presume sia facilmente biodegradabile. MINERAL OIL HYDROTREATYNG	
Si presume che sia " intrinsecamente biodegradabile" . (rif. Olio Minerale Bianco).	
MINERAL OIL HYDROTREATYNG	
Biodegradability: Information not available.	
BUTANE	
Solubility in water.	0,1 - 100 mg/l
Rapidly biodegradable.	
PROPANE	
Solubility in water.	0,1 - 100 mg/l

Rapidly biodegradable.

LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN

Page 10 of 14

Date of print: 13/05/2020 Date of review: 28/09/2016

12.3. Bioaccumulative potential.

NAFTA DI HYDROTREATING Ha potenziale di bioaccumulazione. MINERAL OIL HYDROTREATYNG Ha potenziale di bioaccumulazione, comunque il metabolismo o le proprietà fisiche possono ridurre la bioconcentrazione o limitare la biodisponibilità .(rif. Olio Minerale Bianco).

1,09

BUTANE

Partition coefficient: n- octanol/water.	1,09
octarioi/water.	
PROPANE	

Partition coefficient: noctanol/water.

12.4. Mobility in soil.

NAFTA DI HYDROTREATING Non sono disponibili ulteriori informazioni. MINERAL OIL HYDROTREATYNG Questo materiale ha bassa solubilità e si presume che galleggi e migri dall`acqua al terreno. Si presume che si ripartisca nel sedimento e in solidi sospesi nelle acque reflue. Basso potenziale di migrazione attraverso il suolo. (rif. Olio Minerale Bianco).

12.5. Results of PBT and vPvB assessment.

NAFTA DI HYDROTREATING Non applicabile.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorized waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN

Page 11 of 14

Date of print: 13/05/2020 Date of review: 28/09/2016

ADR / RID, IMDG, 1950 IATA:

14.2. UN proper shipping name.

ADR / RID:	AEROSOLS
IMDG:	AEROSOLS
IATA:	AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es).

ADR / RID:	Class: 2	Label: 2.1	*
IMDG:	Class: 2	Label: 2.1	ð
IATA:	Class: 2	Label: 2.1	2

14.4. Packing group.

ADR / RID, IMDG, -IATA:

14.5. Environmental hazards.

ADR / RID:	NO
IMDG:	NO
IATA:	NO

14.6. Special precautions for user.

ADR / RID:	HIN - Kemler:	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special Provision: -		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 100 Kg	Packaging instructions: 130
	Pass.:	Maximum quantity: 25 Kg	Packaging instructions: 130
	Special Instructions:	A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

SAFEY DATA SHEET in accordance with Regulation (CE) Num. 1907/2006 (REACH)			
LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN	Page 12 of 14	Date of print: 13/05/2020 Date of review: 28/09/2016	
Seveso Category - Directive 2012/18/EC: P3a			
Restrictions relating to the product or contained substances	s pursuant to Annex XVII to EC Regulat	ion 1907/2006.	
Product. Point. 40			
Substances in Candidate List (Art. 59 REACH).			
On the basis of available data, the product does not contain	n any SVHC in percentage greater than	0,1%.	
Substances subject to authorisarion (Annex XIV REACH).			
None.			
Substances subject to exportation reporting pursuant to (E	C) Reg. 649/2012:		
None.			
Substances subject to the Rotterdam Convention:			
None.			
Substances subject to the Stockholm Convention:			
None.			
Healthcare controls.			
Information not available.			
WGK 2: Hazard to waters			
15.2. Chemical safety assessment.			
No chemical safety assessment has been processed for th	e mixture and the substances it contains	S.	
SECTION 16. Other information.			

٦

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Asp. Tox. 1	Aspiration hazard, category 1
Skin Irrit. 2	Skin irritation, category 2

Γ

LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN

Page 13 of 14

Date of print: 13/05/2020 Date of review: 28/09/2016

STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

LUBRIFICANTE ARMI cod. 54262001 Revision: 13 / EN

Page 14 of 14

Date of print: 13/05/2020 Date of review: 28/09/2016

10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament - The Merck Index. - 10th Edition

Handling Chemical Safety

INRS - Fiche Toxicologique (toxicological sheet)

Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12.