USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 1 di 13

 Date of review: 16/01/2019

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: USA WHITE NERO RAL 9005

Cod.: 85410007_USA WHITE SIL.NERO RAL 9005

1.2 Relevant identified uses of the substance or mixture and uses advised against Identified

uses: Acetoxy silicone sealant

Uses advised against: This product is not recommended for all those uses not specifically identified on the label.

1.3 Details of the supplier of the safety data sheet COMPANY IDENTIFICATION

SARATOGA INT. SFORZA SPA VIA EDISON 76 20090 TREZZANO S/NAVIGLIO (MI) ITALY

Customer Information: trading@saratogasforza.com

1.4 EMERGENCY TELEPHONE NUMBER

SARATOGA INT. SFORZA SPA +39 02 445731 from Monday to Friday (h.09:00-13:00 / 14:00-17:30)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008:

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

Precautionary statements

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

Supplemental information

EUH208 Contains: 4,5-Dichloro-2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

Avoid contact with eyes and skin

USA WHITE NERO RAL 9005

cod.85410007

Date of print: 20/08/2019 Date of review: 16/01/2019 Pag. 2 di 13 Versione: 5.0/ EN

2.3 Other hazards

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone elastomer

3.2 Mixtures

This product is a mixture.

CASRN / EC-No. / Index-No.	REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008
CASRN Not available EC-No. 934-956-3 Index-No.	01-2119827000-58	>= 11,0 - <= 16,0 %	Hydrocarbons, C15-C20, n- alkanes, isoalkanes, cyclics, < 0.03% aromatics	Asp. Tox 1 - H304
CASRN Not available EC-No. 927-632-8 Index-No.	01-2119457736-27	>= 2,8 - <= 4,0 %	Hydrocarbons, C14-C18, n- Alkanes, Isoalkanes, Cyclics, <2% Aromatics	Asp. Tox 1 - H304
CASRN 64359-81-5 N. 264-843-8 Index-No.	_	>= 0,0025 - < 0,025 %	4,5-Dichloro-2- octyl-2H- isothiazol-3-one	Acute Tox 4 - H302 Acute Tox 2 - H330 Acute Tox 4 - H312 Skin Corr 1C - H314 Skin Sens 1A - H317 STOT SE - 3 - H335 Aquatic Acute - 1 - H400 Aquatic Chronic - 1 - H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water.

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 3 di 13

 Date of review: 16/01/2019

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

- **4.2 Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.
- **4.3 Indication of any immediate medical attention and special treatment needed Notes to physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical

Unsuitable extinguishing media: None known.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides Silicon oxides Metal oxides Cobalt compounds Nitrogen oxides (NOx) Chlorine compounds

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

5.3 Advice for firefighters

Fire Fighting Procedures: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- **6.1 Personal precautions, protective equipment and emergency procedures:** Follow safe handling advice and personal protective equipment recommendations.
- **6.2 Environmental precautions:** Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 4 di 13
 Date of review: 16/01/2019

6.3 Methods and materials for containment and cleaning up: Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections:

See sections: 7, 8, 11, 12 and 13.

SECTION 7: HANDLING AND STORAGE

- **7.1 Precautions for safe handling:** Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- **7.2 Conditions for safe storage, including any incompatibilities:** Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.

7.3 Specific end use(s): See the technical data sheet on this product for further information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Hydrocarbons, C14-C18, n-	ACGIH	TWA	200 mg/m3 , total
Alkanes, Isoalkanes, Cyclics,			hydrocarbon vapor
<2% Aromatics			
Decamethylcyclopentasiloxa	US WEEL	TWA	10 ppm
ne			

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

8.2 Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 5 di 13
 Date of review: 16/01/2019

Eye/face protection: Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent. **Skin protection**

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

Use the following CE approved air-purifying respirator: Organic vapor cartridge, type A (boiling point >65 °C)

Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties Appearance

Physical state thixotropic paste

Color black

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 6 di 13
 Date of review: 16/01/2019

Odor acetic acid

Odor Threshold

pH

Not applicable

Melting point/range

No data available

No data available

No data available

No data available

Not applicable

Flash point

Not applicable

Evaporation Rate (Butyl Acetate

Not applicable

= 1)

Flammability (solid, gas) Not classified as a flammability hazard

Lower explosion limitNo data availableUpper explosion limitNo data availableVapor PressureNot applicableRelative Vapor Density (air = 1)No data available

Relative Density (water = 1) 0,96

Water solubility

No data available

Partition coefficient: n
No data available

octanol/water

Auto-ignition temperatureNo data availableDecomposition temperatureNo data availableDynamic ViscosityNot applicableKinematic ViscosityNo data availableExplosive propertiesNot explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

9.2 Other information

Liquid Density0,96 g/cm3Molecular weightNo data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: Not classified as a reactivity hazard.

10.2 Chemical stability: Stable under normal conditions.

10.3 Possibility of hazardous reactions: Can react with strong oxidizing agents.

10.4 Conditions to avoid: None known.

10.5 Incompatible materials: Oxidizing agents

10.6 Hazardous decomposition products: Formaldehyde.

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 7 di 13
 Date of review: 16/01/2019

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects Acute toxicity

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 5 000 mg/kg Estimated.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s): LD50, Rabbit, > 2 000 mg/kg Estimated.

Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

Skin corrosion/irritation

Prolonged exposure not likely to cause significant skin irritation.

Prolonged or repeated exposure may cause defatting of the skin leading to drying or flaking of skin.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.

May cause mild eye discomfort.

Sensitization

For skin sensitization:

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant information found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For similar material(s):

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

For this family of materials: Did not cause cancer in long-term animal studies which used routes of exposure considered relevant to industrial handling. Positiveresults have been reported in other studies using routes of exposure not relevant to industrial handling.

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 8 di 13
 Date of review: 16/01/2019

Contains an additional component(s) that is/are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency.

Teratogenicity

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity

For similar material(s): In animal studies, did not interfere with reproduction.

Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, > 5,266 mg/l

Hydrocarbons, C14-C18, n-Alkanes, Isoalkanes, Cyclics, <2% Aromatics

Acute inhalation toxicity

Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed.

For similar material(s): LC50, Rat, 4 Hour, dust/mist, > 5,0 mg/l

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LL50, Scophthalmus maximus (turbot), 96 Hour, 1 028 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

For similar material(s):

EL50, Daphnia magna, static test, 48 Hour, 210 mg/l, OECD Test Guideline 202 LL50, Acartia tonsa, 48 Hour, > 3 193 mg/l, ISO 14669 and PARCOM method

Acute toxicity to algae/aquatic plants

EL50, Skeletonema costatum (marine diatom), 72 Hour, Growth rate, > 10 000 mg/l, ISO 10253

Toxicity to bacteria

Tetrahymena pyriformis, 40 Hour, Growth inhibition

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 9 di 13
 Date of review: 16/01/2019

Hydrocarbons, C14-C18, n-Alkanes, Isoalkanes, Cyclics, <2% Aromatics

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Fish, 96 Hour, > 1 028 mg/l

Acute toxicity to aquatic invertebrates

EC50, Other, 48 Hour, > 3 193 mg/l

Acute toxicity to algae/aquatic plants

EC50, Skeletonema costatum (marine diatom), 72 Hour, > 3 198 mg/l

12.2 Persistence and degradability

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

For similar material(s): **Biodegradation:** 57,5 % **Exposure time:** 28 d

Method: OECD Test Guideline 301F

10-day Window: Fail

Biodegradation: 74 % Exposure time: 28 d

Method: OECD Test Guideline 306

Hydrocarbons, C14-C18, n-Alkanes, Isoalkanes, Cyclics, <2% Aromatics

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready

biodegradability.

Biodegradation: 74 % **Exposure time:** 28 d

12.3 Bioaccumulative potential

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Bioaccumulation: No data available. Not applicable

Hydrocarbons, C14-C18, n-Alkanes, Isoalkanes, Cyclics, <2% Aromatics

Bioaccumulation: No relevant data found.

12.4 Mobility in soil

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Expected to be relatively immobile in soil (Koc > 5000).

Hydrocarbons, C14-C18, n-Alkanes, Isoalkanes, Cyclics, <2% Aromatics

No relevant data found.

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 10 di 13

 Date of review: 16/01/2019

12.5 Results of PBT and vPvB assessment

Hydrocarbons, C14-C18, n-Alkanes, Isoalkanes, Cyclics, <2% Aromatics

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

12.6 Other adverse effects

Hydrocarbons, C14-C18, n-Alkanes, Isoalkanes, Cyclics, <2% Aromatics

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

SECTION 14: TRANSPORT INFORMATION

Classification for ROAD and Rail transport (ADR/RID):

14.1 UN number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable14.4 Packing group Not applicable

14.5 Environmental hazards Not considered environmentally hazardous based on

available data.

14.6 Special precautions for user No data available.

Classification for SEA transport (IMO-IMDG):

14.1 UN number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable14.4 Packing group Not applicable

14.5 Environmental hazards Not considered as marine pollutant based on available data.

14.6 Special precautions for user No data available.

14.7 Transport in bulk according to Annex I or II of MARPOL

73/78 and the IBC or IGC Consult IMO regulations before transporting ocean bulk

Code

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 11 di 13

 Date of review: 16/01/2019

Classification for AIR transport (IATA/ICAO):

14.1 UN number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable
 14.4 Packing group Not applicable
 14.5 Environmental hazards Not applicable
 14.6 Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Reg.UE 528/2012 amended (Biocide Reg.): The product is a treated article according to the biocides regulation, it contains the substance "4,5-Dichloro-2-octyl-2H-isothiazol-3-one" having anti-mold feature. The active substance is currently under review for approval.

REACh Regulation (EC) No 1907/2006

This product contains only components that have been either pre-registered, registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH)., Polymers are exempted from registration under REACH. All relevant starting materials and additives have been either pre-registered, registered, or are exempt from registration to Regulation (EC) No. 1907/2006 (REACH)., The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure thathis/her understanding of the regulatory status of this product is correct.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: Not applicable

15.2 Chemical safety assessment

Not applicable

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 12 di 13

 Date of review: 16/01/2019

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. Acute toxicity
Aquatic Acute Acute aquatic toxicity
Aquatic Chronic Chronic aquatic toxicity
Asp. Tox. Aspiration hazard
Eye Dam. Serious eye damage

Skin Corr. Skin corrosion
Skin Sens. Skin sensitisation

GB EH40 UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA Long-term exposure limit (8-hour TWA reference period)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

This product is not classified as dangerous according to EC criteria.

Revision

Sections from 1 to 16.

Legend

_090a			
ACGIH	USA. ACGIH Threshold Limit Values (TLV)		
TWA	8-hour, time-weighted average		
Asp. Tox.	Aspiration hazard		

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil

USA WHITE NERO RAL 9005

 cod.85410007
 Date of print: 20/08/2019

 Versione: 5.0/ EN
 Pag. 13 di 13

 Date of review: 16/01/2019

Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG -International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: SVHC - Substance of Very High Concern: TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by internal references within our company.

ΙT