XONTÜĞÂÛĞOĞU Þ ÒÁDÞÖWÜQYU

 cod.Ì Í FÏ H€€F
 Date of print: €Í ÐEÏ ÐЀFÌ

 Version: F€ÏF/ EN
 Page 1 of FH
 Date of previous review: FJÐEÏ ÐЀF7

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code: **85173001**

Product name. VIA-SIL SILICONE INDURITO

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use. Remover for cured silicone sealant.

Uses advised against

This product is not recommended for all those industrial, professional or consumer uses not specifically identified on the label.

1.3. Details of the supplier of the safety data sheet.

Name. Saratoga Int. Sforza Spa
Full address. Via Edison 76

District and Country. 20090 Trezzano s/Naviglio (MI)

ITALY

Tel. +039 02.445731 Fax. +039 02.4452742

e-mail address of the competent person.

responsible for the Safety Data Sheet. trading@saratogasforza.com

1.4. Emergency telephone number.

For urgent inquiries refer to. **ΚΕΝΤΡΟ ΔΗΛΗΤΗΡΙΑΣΕΩΝ 210 7793777**

CAV - Ospedale Pediatrico "Bambino Gesù" - Roma - Tel. +39 06 68593726 (h24) CAV - Azienda Ospedaliero-Universitaria Foggia - Foggia - Tel. +39 0881 732326 (h24) CAV - Azienda Ospedaliera "A. Cardarelli" - Napoli - Tel. +39 081 7472870 (h24)

CAV - Policlinico "Umberto I" - Roma - Tel. +39 06 4450618 (h24) CAV - Policlinico "A. Gemelli" - Roma - Tel. +39 06 3054343 (h24)

CAV - Azienda Ospedaliera "Careggi" U.O. Tossicologia Medica - Firenze - Tel. +39 055

7947819(h24)

CAV - Centro Nazionale di Informazione Tossicologica - Pavia - Tel. +39 0382 24444

(h24)

CAV - Ospedale "Niguarda Ca' Granda" - Milano - Tel. +39 02 66101029 (h24)

CAV - Azienda Ospedaliera "Papa Giovanni XXIII" - Bergamo - Tel. +39 800 883300 (h24)

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety data sheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1 H318 Causes serious eye damage. Skin irritation, category 2 H315 Causes skin irritation.

2.2. Label elements.

XQHÜĞÂÛĞĞÛÞÒÁQÞÖWÜQVU

cod.Ì Í FÏ H€€F Date of print: €Í BEÏ BO€FÌ Version: F€È/ EN Page 2 of FH Date of previous review: FJEE EDEF7

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H318 Causes serious eye damage. H315 Causes skin irritation.

Precautionary statements:

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection / face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to P305+P351+P338

do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. P310 Dispose of contents/container to authorized collection centres. P501

Other statements: P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P302+P352 IF ON SKIN: Wash with plenty of soap and water. P332+P313 If skin irritation occurs: Get medical advice/attention.

Contains: Benzenesulfonic, 4-C10-13-sec-alkyl derivs

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.2. Mixtures.

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification.

(CLP).

2-BUTOXYETHANOL

CAS. 111-76-2 $10 \le x < 20$

Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin

Classification 1272/2008

Irrit. 2 H315

EC. 203-905-0 INDEX. 603-014-00-0

cod.Ì Í FÏ H€€F

Date of print: €Í BŒÏ BЀFÌ

Version: F€ÏF/EN

Page 3 of FH

Date of previous review: FJBŒÏ BЀF7

Reg. no. 01-2119475108-36

Benzenesulfonic, 4-C10-13-sec-alkyl derivs

CAS. 85536-14-7 3 ≤ x < 5 Acute Tox. 4 H302, Skin Corr. 1B H314, Aquatic Chronic 3

H412

EC. 287-494-3

Reg. no. 01-2119490234-40

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always

X**O**ŒÙOŠÁÙOŠOÔU ÞÒÁOÞÖWÜQVU cod.Ì Í FÏ H€€F

Date of print: €Í BEÏ BO€FÌ Version: F€È/EN Page 4 of FH Date of previous review: FJEE EDEF7

wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

10

7.3. Specific end use(s).

Shake before use. Viasil is effective only on cured silicone sealant beads provided they are clean and dry.

XQΆÇŠÁÙÇŠQÔUÞÒÁQÞÖWÜQVU

cod.Ì Í FÏ H€€F

Date of print: €Í BEÏ B9€FÌ

Version: F€ÌF/ EN

Page 5 of FH

Date of previous review: FJBEÏ B9€F7

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
TUR	Türkiye	2000/39/EC sayılı Direktifin ekidir
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2016

2-BUTOXYETHANOL								
Threshold Limit Value. Type Country TWA/8h				STEL/15min				
Туре	Country	mg/m3	nnm	mg/m3	nnm			
4004/	DELL		ppm	<u> </u>	ppm	OLCINI		
AGW	DEU	49	10	196	40	SKIN.		
MAK	DEU	49	10	98	20	SKIN.		
VLA	ESP	98	20	245	50	SKIN.		
VLEP	FRA	49	10	246	50	SKIN.		
WEL	GBR	123	25	246	50	SKIN.		
TLV	GRC	120	25					
VLEP	ITA	98	20	246	50	SKIN.		
NDS	POL	98		200				
ESD	TUR	98	20	246	50	SKIN.		
OEL	EU	98	20	246	50	SKIN.		
TLV-ACGIH		97	20					
Predicted no-effect concentra	tion - PNEC.							
Normal value in fresh water Normal value in marine water Normal value for fresh water sediment Normal value for water, intermittent release Normal value of STP microorganisms Normal value for the food chain (secondary poisoning) Normal value for the terrestrial compartment				88 88 346 91 463 2 313		mg/l mg/kg mg/l mg/l mg/kg mg/kg		
Health - Derived no-effect	t level - DNEL / I Effects on	OMEL			Effects on			
Route of exposure	consumers. Acute local	Acute systemic	Chronic local	Chronic systemic	workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.				3.2 mg/kg bw/d				
Inhalation.				49 mg/m3				98 mg/m3
Skin.				38 mg/kg bw/d				75 mg/kg bw/d

XQUEÜĞAÜĞĞQÜÞÒÁQÞÖWÜQYU

cod.ÌÍFÏH€€F

Date of print: €Í BEÏ 809€FÌ

Version: F€ÌE/EN

Page 6 of FH

Date of previous review: FJBeÏ 809€F7

Benzenesulfonic, 4-C10-13-sec-alkyl d	erivs						
Predicted no-effect concentration - PNEC.							
Normal value in fresh water			287		mg/l		
Normal value in marine water		287 mg/					
Normal value for fresh water sediment		28 mg/kg			1		
Normal value for marine water sediment		287 mg/kg					
Normal value for water, intermittent release		167	3 3				
Normal value of STP microorganisms		343 mg/l					
Health - Derived no-effect level - DNE	I / DMFI		0.0		9		
Effects or				Effects on			
consume				workers			
Route of exposure Acute loc		Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
Troute or exposure Troute for	ai riodio o yotoiiiio	Official foods	systemic	710010 10001	systemic	Omorno rocar	systemic
Oral.			0,01011110		o you on mo		0.85 mg/kg/d
							gg
Inhalation.		3 mg/m3	3 mg/m3				
Skin.			85 mg/kg/d			12 mg/kg/d	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

TLV of solvent mixture: 97 mg/m3.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

XQHÉ)ĞÁQÓUÞÒÁQÞÖWÜQVU

cod.Ì Í FÏ H€€F Date of print: €Í ÐEÏ ÐЀFÌ
Version: F€ÌF/ EN Page 7 of FH Date of previous review: FJÐEÏ ÐЀF7

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance light gray Colour charactéristic Odour Not available. Odour threshold. Acid pH. Not available. Melting point / freezing point. 170 °C. Initial boiling point. Not available. Boiling range. 65 °C. Flash point. Evaporation Rate Not available. Flammability of solids and gases Not available

Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Vapour density Not available. Relative density. ca. 1,05 Solubility insoluble Partition coefficient: n-octanol/water N.D. 240 °C. Auto-ignition temperature. Decomposition temperature. N.D.

Viscosity >20,5 mm2/sec (40°C) Explosive properties not applicable Oxidising properties not applicable

9.2. Other information.

Total solids (250°C / 482°F) 80,10 % VOC (Directive 2010/75/EC) : 10,00 % VOC (volatile carbon) : 6,09 %

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

XQUEÜÇĞÁÜÇĞQÖUÞÒÁQÞÖWÜQYU

cod.Ì Í FÏ H€€F

Date of print: €Í BEÏ B0€FÌ

Version: F€ÌF/EN

Page 8 of FH

Date of previous review: FJ BEÏ B0€F7

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-BUTOXYETHANOL

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials.

Do not apply on water and wet surfaces; the effectiveness is reduced and corrosion could start on metal surfaces.

10.6. Hazardous decomposition products.

2-BUTOXYETHANOL May develop: hydrogen.

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:> 20 mg/l

LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component).

LD50 (Oral) of the mixture:>2000 mg/kg

LD50 (Dermal) of the mixture:>2000 mg/kg

2-BUTOXYETHANOL

LD50 (Oral).615 mg/kg Rat

LD50 (Dermal).405 mg/kg Rabbit

LC50 (Inhalation).2,2 mg/l/4h Rat

SKIN CORROSION / IRRITATION.

XQHÜĞĞÜĞĞÜL ÞÖÁQÞÖWÜQVU

cod.ÌÍFÏH€€F

Date of print: €ÍBEÏB9€FÌ

Version: F€ÈF/EN

Page 9 of FH

Date of previous review: FJBEÏB9€F7

Causes skin irritation.

SERIOUS EYE DAMAGE / IRRITATION.

Causes serious eye damage.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm2/sec (40°C).

SECTION 12. Ecological information.

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

2-BUTOXYETHANOL

Solubility in water. 1000 - 10000 mg/l

Rapidly biodegradable.

12.3. Bioaccumulative potential.

2-BUTOXYETHANOL

Partition coefficient: n- 0,81

octanol/water.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

XQHEUĞÁUĞĞQÜU Þ ÒÁQÞ ÖWÜQYU cod.Ì Í FÏ H€€F

Date of print: €Í BEÏ BO€FÌ Version: F€E/EN Page 10 of FH Date of previous review: FJ⊞ ED€F7

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.
14.1. UN number.
Not applicable.
14.2. UN proper shipping name.
Not applicable.
14.3. Transport hazard class(es).
Not applicable.
14.4. Packing group.
Not applicable.
14.5. Environmental hazards.
Not applicable.
14.6. Special precautions for user.
Not applicable.
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

XODEÜĞÂÜĞĞÖÜÞÒÁODÖWÜQVU

 cod.Ì Í FÏ H€€F
 Date of print: €Í ÐEÏ ÐSEFÌ

 Version: F€ÏF/ EN
 Page 11 of FH
 Date of previous review: FJÐEÏ ÐSEF7

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC:

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point.

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

3

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

WGK 1: Low hazard to waters

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Acute toxicity, category 4
Skin Corr. 1B Skin corrosion, category 1B

XONEÜÇĞÂÛÇĞOÛU Þ ÒÁQÞÖWÜQVU

Date of print: €Í ÐEÏ ÐЀFÌ cod.Ì Í FÏ H€€F Date of previous review: FJEE EDEF7 Version: F€È/EN Page 12 of FH

Eye Dam. 1 Serious eve damage, category 1

Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2

Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H302 Harmful if swallowed

H312 Harmful in contact with skin.

H332 Harmful if inhaled

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

Causes skin irritation H412 Harmful to aquatic life with long lasting effects.

LEGEND:

H315

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008 DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- · The Merck Index. 10th Edition · Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition

XQHÜĞĞÂÛĞĞQÛ ÞÒÁQÞÖWÜQYU cod.Ì Í FÏ H€€F

Date of print: €Í BEÏ BO€FÌ Page 13 of FH Version: F€È/EN Date of previous review: FJ⊞ ED€F7

- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:
The following sections were modified
01 /02 /09